

The CUE Series is a family of ultra-slim, high-performance installation loudspeakers designed for spaces where sound quality must coexist with architecture. Built for bars, restaurants, clubs, cultural venues, and public interiors, CUE delivers controlled, even coverage with exceptional speech intelligibility and musical clarity.


The slim-format enclosure minimizes visual impact while advanced transducer alignment ensures consistent sound across the listening area. Available in surface-mount and hidden in-wall versions, CUE adapts seamlessly to both expressive and invisible installations. Paired with the dedicated CUE SUB, the system scales from elegant background audio to confident, full-range performance.

CUE Si is the in-wall version of CUE S, designed for fully concealed installations behind acoustically transparent surfaces. Using the same dual 2" woofers, passive radiators, and 1" high-frequency driver as the surface-mounted model, CUE Si delivers identical tonal balance and clarity without visual presence. Ideal for architecturally pure spaces where sound must be heard but never seen.

Available in black.



DIMENSIONS



SPECIFICATIONS

Frequency Response (-10dB)	150 - 25000 Hz
Max SPL ¹ (nominal / peak)	105 dB / 111 dB
Sensitivity (1W / 1m)	88 dB
LF driver	2 x 2" woofer, 2 x passive radiator
HF driver	1" tweeter
Nominal Coverage Angle	120° horizontal
Impedance	4 Ohm
Nominal power ²	50 W
Connectors	Phoenix
Dimensions (W x D x H)	61 x 45 x 454 mm / 2.40" x 1.78" x 17.87"
Weight / Shipping	1,44 kg; 3.17 lbs / 1,94 kg; 4.28 lbs
Mounting options	2 x holes for mounting
Enclosure material	Steel, wear-resistant paint

¹ - pink noise, filtered according to AES 2 - 2012, crest factor 12 dB

² - based on transducer power measured according to AES 2 - 2012

CONNECTIONS

Signal +	+ terminal
Signal -	- terminal
High pass filter:	
Freq, no less than	150 Hz
Order, no less than	18 dB/oct
Recommended amplifier power	50 - 100 W on nominal impedance

SAFETY INSTRUCTIONS

1. Keep liquids, direct sunlight, open flames, and heat sources away from the speaker system to prevent damage or failure.
2. Avoid using the system with damaged connectors or cables to prevent electrical shock or fire hazards.
3. Ensure the speaker is securely positioned on a stable surface (floor, stage, or wall).
4. On angled or slippery surfaces, secure the system to prevent movement caused by vibration.
5. Limit exposure to sound levels above 90 dB to prevent potential hearing damage.
6. Use a high-pass filter (HPF) to eliminate low, non-audible frequencies and avoid speaker damage and sound distortion.
7. Do not exceed the input power ratings specified to ensure safe and reliable operation of the speaker system.