



# NX 10i

## FULL-RANGE PASSIVE INSTALLATION SPEAKER

NX series represents solid and powerful solutions for fixed installations as well as demanding mobile sound applications. NX full-range cabinets are based on top-line neodymium magnet transducers and high frequency drivers fitted with demodulation rings and copper caps for less distortions and improved voice coil cooling, allowing for prolonged high-SPL operation while preserving clarity and intelligibility.

NX 10i is a dedicated installation speaker with wide range of accessories for flexible installation options. NX 10i is optionally available as waterproof, and equipped with barrier strip terminals for simple and cost-friendly connections.



### Main features:

- 500 W nominal power
- 10" woofer with 3" voice coil
- 1,5" HF driver with 2,8" voice coil
- 133 dB Max SPL
- M10 mounting points

Frequency Response (-10dB)	65 - 19000 Hz
Max SPL <sup>1</sup>	133 dB
Sensitivity (1W/1m)	97 dB
LF Driver	10", 3" VC
HF Driver	1,5", 2,8" VC
Nominal Coverage Angle (Horizontal × Vertical)	80 × 70 deg
Impedance	8 Ohm
Nominal power <sup>2</sup>	500 W
Connectors	Barrier strip
Dimensions (W×H×D), mm	319x610x336 mm
Net weight, kg	19 kg
Shipping weight, kg	22 kg
Mounting	10x M10 mounting points, 35mm pole socket
Enclosure material	Plywood; wear-resistant paint
Grill	Steel grill, polymer protective net

<sup>1</sup> - peak value, calculated according to AES 2 - 2012

<sup>2</sup> - based on transducer power measured according to AES 2 - 2012

With dedication to constant improvement of the products, manufacturer may change the listed specifications without prior notice