

NX series represents solid and powerful solutions for fixed installations as well as demanding mobile sound applications. NX fullrange cabinets are based on top-line neodymium magnet transducers and high frequency drivers fitted with demodulation rings and copper caps for less distortions and improved voice coil cooling, allowing for prolonged high-SPL operation while preserving clarity and intelligibility.

NX 15 is a passive speaker based on 15" cone transducer and 1,5" HF driver. Speaker is equipped with pole mount adapter and M10 mounting points for various installaiton purposes and carefully designed crossover network for ease of setup and use.



Main features:

- 500W nominal powe
- \cdot 15" woofer with 3" voice coil
- 1,5" HF driver with 2,8" voice coi
- · 134 5 dB Max SPL
- Pole mount adapter, M10 mounting points

Frequency Response (-10dB)	50 - 19000 Hz
Max SPL ¹	134,5 dB
Sensitivity (1W/1m)	98,5 dB
LF Driver	15", 3" VC
HF Driver	1,5", 2,8" VC
Nominal Coverage Angle (Horizontal × Vertical)	80 x 70 deg
Impedance	8 Ohm
Nominal power ²	500 W
Connectors	2x NeutrikSpeakon
Dimensions (W×H×D)	436x740x423 mm
Net weight	26 kg
Shipping weight	29 kg
Mounting	10x M10 mounting points, 35mm pole socket
Enclosure material	Plywood; wear-resistant paint
Grill	Steel grill, polymer protective net

¹ - peak value, calculated according to AES 2 - 2012

² - based on transducer power measured according to AES 2 - 2012

With dedication to constant improvement of the products, manufacturer may change the listed specifications without prior notice