
## SUB C15


## **PASSIVE SUBWOOFER**


Subwoofer series takes advantage of tremendous experience in touring, installation and mobile markets. Cabinets are equipped with nexttransducers generation reinforced moving system capable of withstanding tremendous pressure and excursion while keeping distortion in check.

Sub C15 is a dedicated arrayble subwoofer with integrated flying hardware, compatible with Cluster Q, Q4 and Q8 full-range cabinets. It is equipped with high-power 15" woofer installed into effective vented enclosure.









## Main features:

integraced trying hardware	
Frequency Response (-10dB)	37 - 300 Hz
Max SPL <sup>1</sup>	133 dB
Sensitivity (1W/1m)	94 dB
LF Driver	15", 4" VC
Impedance	8 Ohm
Nominal power <sup>2</sup>	1000 W
Connectors	4x NeutrikSpeakon
Dimensions (W×H×D), mm	480x508x517 mm
Net weight, kg	38 kg
Shipping weight, kg	41 kg
Mounting	Intergrated flying hardware
Enclosure material	Plywood; wear-resistant paint
Grill	Steel grill, acoustically transparent foam

<sup>&</sup>lt;sup>1</sup> - peak value, calculated according to AES 2 - 2012

<sup>&</sup>lt;sup>2</sup> - based on transducer power measured according to AES 2 - 2012