

SUB H28


PASSIVE SUBWOOFER

Subwoofer series takes advantage of tremendous experience in touring, installation and mobile markets. Cabinets are equipped with next-generation transducers with reinforced moving system capable of withstanding tremendous pressure and excursion while keeping distortion in check.

Sub H28 is a extremly high-output hybrid horn subwoofer designed for touring and high-profile installations, and capable with Hornet line array. It is equipped with two high excursion neodymium 18" woofers, capable of delivering up to 149 dB of SPL.









Main features:

- · 2900W nominal power
- · Two 18" woofer with 4,5" voice coi
- · Efficient hybrid harn design
- · 149.5 dB Max SPL
- · Integrated flying hardware

integraced trying hardware	
Frequency Response (-10dB)	28 - 120 Hz
Max SPL ¹	149,5 dB
Sensitivity (1W/1m)	106 dB
LF Driver	2x 18", 4,5" VC
Impedance	4 Ohm
Nominal power ²	2900 W
Connectors	4x NeutrikSpeakon
Dimensions (W×H×D), mm	744x984x938 mm
Net weight, kg	115 kg
Shipping weight, kg	120 kg
Mounting	Intergrated mounted hardware
Enclosure material	Plywood; wear-resistant paint
Grill	Steel grill, acoustically transparent foam

¹ - peak value, calculated according to AES 2 - 2012

² - based on transducer power measured according to AES 2 - 2012