

# Speakers

## Speaker Systems

### SMB-130/WS

Order No. 0090490



#### Pair of slimline speaker systems, 20 W, 4 Ω

- 2-way system with neodymium bass-midrange speaker and dome tweeter
- Integrated wall holder
- Unobtrusive design with a very pleasant radiation and good level stability
- Perfectly suitable for any background PA application, also excellent as a rear speaker in surround systems



Model	SMB-130/WS
Total power rating	40 W
Power rating (RMS)	20 W
Frequency range	80-18,000 Hz
Sensitivity	88 dB/W/m
Dimensions	185 x 275 x 38 mm
Weight	2.078 kg (pair)

### MKS-42/SW

Order No. 0131520



### MKS-42/WS

Order No. 0131530



#### Pairs of universal 2-way speaker systems, 20 W, 4 Ω

- Black (SW) or white (WS) plastic cabinet with metal front grille
- Integrated holder for wall mounting
- Pivoting mounting bracket



Model	MKS-42/SW, MKS-42/WS
Total power rating	40 W
Power rating (RMS)	20 W
Frequency range	80-18,000 Hz
Dimensions	95 x 150 x 82 mm
Weight	1.4 kg (pair)
Inputs	spring-load, speaker term.

### GLS-351/GR

Order No. 0163080



### GLS-301/GR

Order No. 0163070



#### Weatherproof PA garden speaker „Rock“, stone look, for general PA applications, e.g. in gardens, hotels, restaurants and pubs.

- GLS-301/GR with omnidirectional radiation pattern
- 100 V line technique or 8 Ω operation
- Robust, glass fibre reinforced plastic cabinet
- 2-way coaxial speaker system (200 mm bass speaker and 13 mm tweeter)
- Integrated audio transformer with 4 power taps (30/20/10/5 W)
- Connection cable with luster terminals



Model	GLS-351/GR	GLS-301/GR
Total power rating	90 W	90 W
Power rating (RMS)	30/20/10/5 W (100 V) 45 W (8 Ω)	30/20/10/5 W (100 V) 45 W (8 Ω)
Frequency range	60-20,000 Hz	60-20,000 Hz
Sensitivity	88 dB/W/m	85 dB/W/m
Protection class	IP55	IP55
Admiss. ambient temp.	-20 °C to +50 °C	-20 °C to +50 °C
Dimensions	370 x 300 x 300 mm	320 x 500 x 310 mm
Weight	5.8 kg	9.5 kg