

# Speakers

## Speaker Systems

### WALL-05SET/WS

Order No. 0130132



#### Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integrated 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- 13 cm (5") bass speaker system and dome tweeter
- Mounting bracket for pivoting and tilting

Model	WALL-05SET/WS
Total output power	2 x 50 W
Power rating (RMS)	2 x 30 W
Frequency range	80-20,000 Hz
Input signal	500 mV/20 kΩ (unbal.) 660 mV/40 kΩ (bal.)
Sensitivity	89 dB/W/m
Power supply	~ 230 V/50 Hz/100 VA
Dimensions	163 x 252 x 203 mm (with bracket)
Weight	5.5 kg (pair)
Inputs	1 x RCA L/R (unbalanced) 1 x terminal L/R (balanced) spr.-load speak. term. (passive speaker system) spr.-load speak. term.



### WALL-06SET/WS

Order No. 0130131



#### Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integrated 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- Built-in power supply with 3-pin IEC jack
- 16 cm (6") bass speaker system and dome tweeter
- Mounting bracket for pivoting and tilting

Model	WALL-06SET/WS
Total output power	2 x 50 W
Power rating (RMS)	2 x 30 W
Frequency range	70-20,000 Hz
Input signal	890 mV/20 kΩ (unbal.) 1,600 mV/40 kΩ (bal.)
Sensitivity	90 dB/W/m
Power supply	~ 230V/50 Hz/140VA
Dimensions	196 x 303 x 250 mm (with bracket)
Weight	8 kg (pair)
Inputs	1 x RCA L/R (unbalanced) 1 x terminal L/R (balanced) spr.-load. speak. term. (passive speaker system) spr. load. speak. term.



### MKA-50SET/SW

Order No. 0132350



### MKA-50SET/WS

Order No. 0132360



#### Active 2-way stereo speaker systems, 2 x 20 W

- Set consists of an active and a passive speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Active speaker system with integrated 2-channel amplifier and power supply
- Speakers with magnetic shielding
- Auto-standby function
- Volume control and 2-way tone control

Model	MKA-50SET/SW, MKA-50SET/WS
Total output power	2 x 40 W
Power rating (RMS)	2 x 20 W
Frequency range	60-20,000 Hz
Input signal	420 mV/24 kΩ
Sensitivity	89 dB/W/m
Power supply	~ 230 V/50 Hz/110 VA
Dimensions	180 x 250 x 160 mm
Weight	5.9 kg (pair)
Inputs	1 x RCA L/R (active speak. system only) 1 x 3.5 mm jack screw terminals (both speaker systems)



### MKA-60SET/SW

Order No. 0131580



### MKA-60SET/WS

Order No. 0131590



#### Active 2-way stereo speaker systems, 2 x 15 W

- Set consists of an active and a passive speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Active speaker system with integrated 2-channel amplifier, stereo RCA input, volume control and 2-way tone control, built-in power supply with 3-pin IEC jack
- 16 cm (6½") bass speaker system and dome tweeter

Model	MKA-60SET/SW, MKA-60SET/WS
Total output power	2 x 25 W
Power rating (RMS)	2 x 15 W
Frequency range	45-20,000 Hz
Input signal	400 mV/10 kΩ
Sensitivity	89 dB/W/m
Power supply	~ 230 V/50 Hz/75 VA
Dimensions	220 x 293 x 170 mm
Weight	8 kg (pair)
Inputs	1 x RCA L/R (active speaker system only) spring-load. speaker term. (link, both speaker systems)

