
## **IT-400TW**

Order No. 0162580





- 100 V line technique with very high tapping power
- Weatherproof and IP66 certified
- Very wideband sound with a distinct bass volume, even at very high volume levels
- 16 cm bass-midrange speaker and 25 mm (1") horn
- Robust plastic housing
- Supplied with mounting bracket and screws made of stainless steel







Model	IT-400TW
Power rating (RMS)	60/30/15/7.5 W
Frequency range	100-20,000 Hz
Sensitivity	98 dB/W/m
Beam angle	H: 100°/V: 60°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	420 x 335 x 400 mm
Weight	6.68 kg

## **IT-400RTW**

Order No. 0163350



## Weatherproof horn speaker (music horn),

## 2-way technology

- 100 V line technique with very high tapping power
- Weatherproof and IP66 certified
- Very wideband sound with a distinct bass volume, even at very high volume levels
- 16 cm bass-midrange speaker and 25 mm (1") horn
- Suitable for indoor and outdoor applications
- Due to round design, consistent radiation pattern in the required area, e.g. ceiling suspension in halls
- Robust plastic housing
- Supplied with mounting bracket and screws made of stainless steel

Model	IT-400RTW
Power rating (RMS)	60/30/15/7.5 W
Frequency range	120-20,000 Hz
Sensitivity	101 dB/W/m
Beam angle	H: 90°/V: 90°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 400 mm x 420 mm
Weight	6.5 kg





Professional
PA Solutions
for Your Project



Your Project is our Project