

IT-35

Order No. 0160870



Weatherproof horn speaker

- 100 V line technique
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Robust plastic housing
- Mounting bracket and screws made of stainless steel
- 5-step power selector switch

Model	IT-35
Power rating (RMS)	25/20/15/10/5 W
Frequency range	250-10,000 Hz
Sensitivity	108 dB/W/m
Beam angle	H: 110°/V: 52°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	300 x 180 x 315 mm
Weight	2.4 kg



IT-33

Order No. 0162190



Weatherproof horn speaker

- 100 V line technique
- IP54 tested
- White ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Particularly high power capability in relation to its size
- Suitable for general indoor and outdoor applications
- Integrated high-pass filter for optimising the sound and stability

Model	IT-33
Power rating (RMS)	25/12.5/6.25 W
Frequency range	500-13,000 Hz
Sensitivity	107 dB/W/m
Beam angle	H: 90°/V: 90°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 130 mm x 175 mm
Weight	1.8 kg



IT-32EN

Order No. 0160020



IT-15EN

Order No. 0160230



Weatherproof horn speakers, with EN 54-24 certification.

- 100 V line technique
- IP66 tested
- Light grey ABS housing (self-extinguishing, complies with the standard UL 94V-0)
- Cable inlet via high-strength cable gland

Model	IT-32EN	IT-15EN
Total power rating	30 W	15 W
Power rating (RMS)	30/15/7.5 W	15/7.5/3.75 W
Frequency range	350-10,000 Hz	350-10,000 Hz
Sensitivity	110 dB/W/m	110 dB/W/m
Beam angle	H: 110°/V: 55°	H: 110°/V: 55°
Admiss. ambient temp.	-25 °C to +70 °C	-25 °C to +70 °C
Dimensions	180 x 120 x 230 mm	180 x 120 x 230 mm
Weight	2.1 kg	2.1 kg

- Integrated high-pass filter for optimising the sound and stability
- Supplied with mounting bracket



IT-30

Order No. 0160670



Weatherproof horn speaker

- 100 V line technique
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Aluminium housing
- Mounting bracket and screws made of stainless steel
- 4-step power selector switch

Model	IT-30
Power rating (RMS)	20/15/10/5 W
Frequency range	250-10,000 Hz
Sensitivity	108 dB/W/m
Beam angle	H: 80°/V: 80°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 265 mm x 310 mm
Weight	2.25 kg



IT-20

Order No. 0160660



Weatherproof horn speaker

- 100 V line technique
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Robust plastic housing
- Mounting bracket and screws made of stainless steel
- 4-step power selector switch

Model	IT-20
Power rating (RMS)	15/10/5/2.5 W
Frequency range	275-7,000 Hz
Sensitivity	106 dB/W/m
Beam angle	H: 100°/V: 50°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	250 x 145 x 300 mm
Weight	1.88 kg

