

Speakers

Horn Speakers

UHC-30

Order No. 0160640



Weatherproof horn speaker

- 8 Ω speaker system
- IP66 tested, protected against powerful water jets
- For open-air events, industrial use, in workshops
- Mounting bracket and screws made of stainless steel

Model	UHC-30
Total power rating	40 W
Power rating (RMS)	20 W
Frequency range	230-10,000 Hz
Sensitivity	108 dB/W/m
Beam angle	H: 75°/V: 75°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 310 mm x 285 mm
Weight	1.89 kg



NR-25KS

Order No. 0160240



Horn speaker

- Moisture-proof
- 8 Ω speaker system

Model	NR-25KS
Total power rating	30 W
Power rating (RMS)	15 W
Frequency range	350-8,000 Hz
Sensitivity	102 dB/W/m
Admiss. ambient temp.	0-40 °C
Dimensions	200 x 140 x 235 mm
Weight	1.1 kg



NR-24KS

Order No. 0161020



Horn speaker

- Moisture-proof
- 8 Ω speaker system

Model	NR-24KS
Total power rating	30 W
Power rating (RMS)	15 W
Frequency range	400-7,000 Hz
Sensitivity	105 dB/W/m
Admiss. ambient temp.	0-40 °C
Dimensions	200 x 150 x 235 mm
Weight	0.9 kg



NR-22KS

Order No. 0161010



Horn speaker

- Moisture-proof
- 8 Ω speaker system

Model	NR-22KS
Total power rating	15 W
Power rating (RMS)	8 W
Frequency range	600-7,000 Hz
Sensitivity	104 dB/W/m
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 135 mm x 165 mm
Weight	0.427 kg

