

Portable PA Systems Systems

TXA-700USB

Order No. 0174750



Portable amplifier system, with wireless microphone, integrated Bluetooth receiver and USB/SD card player.

- High-performance class D version 80 W, with optimum efficiency
- Operation via mains connection or built-in lead gel battery 2 x 12 V/5 Ah (operating time: up to 6 hours), integrated automatic battery charging
- For mobile applications, e.g. sales events, lectures
- Wireless microphone with adjustable wireless UHF receiver
- Bluetooth receiver for wireless connection of portable audio players
- Adjustable USB/SD card player with connection for external storage media
- Remote control
- 2-way speaker system
- 2 adjustable inputs via comb. jacks (XLR/6.3 mm jack), switchable mic/line
- 1 aux input (3.5 mm jack, RCA)
- Adjustable reverb
- Common master control with 2-way tone control
- 1 line output (6.3 mm jack)

Model	TXA-700USB
Rated power (P _{RMS})	80 W
Peak output power	120 W
Frequency range	55-20,000 Hz
Carrier frequency	863-865 MHz
Inputs	10 mV (mic), 950 mV (line), 1.4 V (aux)
Equalizer, bass	± 12 dB/55 Hz
Equalizer, treble	± 12 dB/15 kHz
Power supply	~ 230 V/50 Hz/40 VA, rech. battery: 2 x 12 V/5 Ah
Dimensions	360 x 560 x 325 mm
Weight	17 kg
Connections	2 x XLR/6.3 mm jack (mic/line), 1 x RCA L/R (aux), 1 x 3.5 mm jack (aux), 1 x 6.3 mm jack (line out)

- Due to integrated extractable telescopic handle and 2 castors, amplifier system can easily be pulled like a trolley
- Stand sleeve

Licence-free in the EU.



TXA-15USB

Order No. 0173150



Portable amplifier system, with integrated Bluetooth receiver and USB/SD card player.

- Operation via mains connection or built-in lead gel battery 12 V/7.2 Ah (operating time: up to 6 hours), integrated automatic battery charging
- For mobile applications, e.g. sales events, lectures
- Bluetooth receiver for wireless connection of portable audio players
- Adjustable USB/SD card player with connection for external storage media
- 2-way speaker system
- 1 adjustable balanced microphone input via XLR, 1 adjustable microphone input via 6.3 mm mono jack, 1 adjustable CD/Tape input via RCA
- Adjustable master output with 3-way equalizer
- Link connection (6.3 mm jack) for combining several TXA-15USB systems
- Cabinet in flight case design, with drop handles
- Due to integrated extractable telescopic handle and 2 castors, amplifier system can easily be pulled like a trolley
- Stand sleeve

Model	TXA-15USB
Rated power (P _{RMS})	15 W
Peak output power	20 W
Frequency range	70-20,000 Hz
Inputs	6 mV (mic), 600 mV (line)
Link	380 mV
Equalizer, bass	± 15 dB/100 Hz
Equalizer, midrange	± 15 dB/2.5 kHz
Equalizer, treble	± 15 dB/10 kHz
Power supply	~ 230 V/50 Hz/60 VA, rech. battery: 12 V/7.2 Ah
Dimensions	410 x 470 x 310 mm
Weight	16.4 kg
Connections	1 x XLR (mic), 1 x 6.3 mm jack (mic), 1 x RCA L/R (line), 1 x 6.3 mm jack (link)

