

Speakers

Column Speakers

ETS-8100TW/SW

Order No. 0163790



ETS-8100TW/WS

Order No. 0163800



High-quality weatherproof PA column speaker,

IP66

- High-quality 2-way column speaker with excellent sound characteristics
- 100 V line technique or 8 Ω operation
- 8 x 7.7 cm (3") speaker with polypropylene cone
- 25 mm (1") centrally arranged dome tweeter
- 3 power taps: 60/30/15 W
- Power capability: 100 W in 8 Ω operation
- Connection is made via cable with high-strength cable gland (length: 2 m)
- Robust aluminium cabinet with plastic front protective grille
- Supplied with robust wall bracket for pivoting and tilting



Model

ETS-8100TW/SW

ETS-8100TW/WS

Power rating (RMS)	60/30/15 W (100 V) 100 W (8 Ω)	60/30/15 W (100 V) 100 W (8 Ω)
Frequency range	110-20,000 Hz	110-20,000 Hz
Number of speakers	9	9
Sensitivity	95 dB/W/m	95 dB/W/m
Beam angle	H: 70°/V: 20°	H: 70°/V: 20°
Admiss. ambient temp.	0-40 °C	0-40 °C
Dimensions	125 x 869 x 110 mm	125 x 869 x 110 mm
Weight	6 kg	6 kg

ETS-8060TW/SW

Order No. 0163770



ETS-8060TW/WS

Order No. 0163780



PA hi-fi column speaker

- High-quality 2-way column speaker with excellent sound characteristics
- 100 V line technique or 8 Ω operation
- 4 x 5 cm (2") full range speaker with paper cone
- 25 mm (1") centrally arranged dome tweeter
- 3 power taps: 20/10/5 W
- Power capability: 40 W in 8 Ω operation
- Connection is made via cable with high-strength cable gland (length: 2 m)
- Robust aluminium cabinet of an appealing design with cloth-covered plastic front protective grille
- Supplied with pivoting and tiltable wall bracket



Model

ETS-8060TW/SW

ETS-8060TW/WS

Power rating (RMS)	20/10/5 W (100 V) 40 W (8 Ω)	20/10/5 W (100 V) 40 W (8 Ω)
Frequency range	160-20,000 Hz	160-20,000 Hz
Number of speakers	5	5
Sensitivity	89 dB/W/m	89 dB/W/m
Beam angle	H: 180°/V: 40°	H: 180°/V: 40°
Dimensions	85 x 430 x 70 mm	85 x 430 x 70 mm
Weight	2.5 kg	2.5 kg