

EUL-80/SW

Order No. 0161190



EUL-80/WS

Order No. 0161230



EUL-60/SW

Order No. 0161170



EUL-60/WS

Order No. 0161180



EUL-30/SW

Order No. 0161150



EUL-30/WS

Order No. 0161160



Pair of universal PA speaker systems

- 100 V line technique, 2-way version
- EUL-80... with a 25 mm dome tweeter, EUL-60... and EUL-30... with an 11 mm dome tweeter
- Excellent sound quality
- 6-step power selector switch
- Black (SW) or white (WS) plastic cabinet
- Pivoting mounting bracket
- Beveled shape of cabinets also allows mounting in corners

Model	EUL-80/SW, EUL-80/WS	EUL-60/SW, EUL-60/WS	EUL-30/SW, EUL-30/WS
Power rating (RMS)	30/15/7.5/4/2 W	15/7.5/4/2/1 W	15/7.5/4/2/1 W
Frequency range	40-20,000 Hz	60-20,000 Hz	80-20,000 Hz
Sensitivity	89 dB/W/m	89 dB/W/m	87 dB/W/m
Dimensions	270 x 370 x 220 mm	215 x 290 x 172 mm	130 x 192 x 115 mm
Weight	5.4 kg	3.4 kg	3.3 kg (pair)
Inputs	spring-load, speaker term.	spring-load, speaker term.	spring-load, speaker term.

PAB-82WP/WS

Order No. 0253590



Weatherproof high-performance PA speaker system, 120 W

- 2-way coaxial speaker system in an ABS cabinet
- 20 cm (8") PA coaxial system with impregnated paper cone
- Coaxially integrated 25 mm (1") horn tweeter
- Front grille with water-repellent gauze
- Recessed connection terminal with cover plate and high-strength cable gland
- Metal parts and wall bracket made of stainless steel

- Ball-proof according to DIN 18032, Part 3

Model	PAB-82WP/WS
Total power rating	240 W
Power rating (RMS)	120/60/30 W
Impedance	8 Ω
Frequency range	50-20,000 Hz
Sensitivity	96 dB/W/m
Protection class	IP45
Admiss. ambient temp.	-10 °C to +40 °C
Dimensions	280 x 280 x 270 mm
Weight	9.5 kg



PAB-52WP/WS

Order No. 0253580



Weatherproof high-performance PA speaker system, 50 W

- Wideband bass-reflex system in an ABS cabinet
- 100 V or 4 Ω operation, selectable
- 13 cm (5") high-quality full range speaker with aluminium cone
- Front grille with water-repellent gauze
- Metal parts and wall bracket made of stainless steel
- Ball-proof according to DIN 18032, Part 3

Model	PAB-52WP/WS
Power rating (RMS)	50/25/12.5 W
Impedance	4 Ω
Frequency range	60-18,000 Hz
Number of speakers	1
Sensitivity	87 dB/W/m
Protection class	IP45
Admiss. ambient temp.	-10 °C to +40 °C
Dimensions	200 x 200 x 190 mm
Weight	5.1 kg



ESP-305/WS

Order No. 0163250



Miniature PA speaker systems

- 100 V PA speaker system
- 13 cm (5") full range speaker
- Power taps: 20/10/5 W
- Multi-purpose installation options
- 4 x M8 threaded inserts
- 2 x M6 threaded inserts, suitable e.g. for support LST-40
- Use of subwoofer systems is recommended
- Supplied with mounting bracket

Model	ESP-305/WS
Power rating (RMS)	20/10/5 W
Frequency range	140-18,000 Hz
Number of speakers	1
Sensitivity	93 dB/W/m
Dimensions	147 x 146 x 152 mm
Weight	1.2 kg

