

PAB-12WP/SW

Order No. 0253740



Weatherproof high-performance PA speaker system, 200 W, 8 Ω

- 2-way bass-reflex system in an ABS cabinet
- 30 cm (12") PA bass speaker with impregnated paper cone
- 25 mm (1") horn tweeter system
- Front grille with water-repellent gauze
- Metal parts made of stainless steel
- 4 x M10 threaded insert each at the top and bottom for suspended installation
- Stand sleeve
- Ball-proof according to DIN 18032, Part 3

Model	PAB-12WP/SW
Total power rating	400 W
Power rating (RMS)	200 W
Frequency range	42-20,000 Hz
Sensitivity	98 dB/W/m
Protection class	IP45
Admiss. ambient temp.	-10 °C to +40 °C
Dimensions	370 x 655 x 410 mm
Weight	20.32 kg
Inputs	1 x SPEAKER
Outputs	1 x SPEAKER, par. out



PAB-8WP/WS

Order No. 0253570



Weatherproof high-performance PA speaker system, 120 W

- 2-way bass-reflex system in an ABS cabinet
- 100 V or 8 Ω operation, selectable
- 20 cm (8") PA bass speaker with impregnated paper cone
- 25 mm (1") horn tweeter system
- Front grille with water-repellent gauze
- Metal parts and wall bracket made of stainless steel
- Ball-proof according to DIN 18032, Part 3

Model	PAB-8WP/WS
Total power rating	240 W
Power rating (RMS)	120/60/30 W
Frequency range	48-20,000 Hz
Sensitivity	96 dB/W/m
Protection class	IP45
Admiss. ambient temp.	-10 °C to +40 °C
Dimensions	240 x 430 x 250 mm
Weight	11.42 kg
Inputs	1 x SPEAKER, screw terminal
Outputs	1 x SPEAKER, par. out



PAB-6WP/WS

Order No. 0253560



Weatherproof high-performance PA speaker system, 100 W

- Compact 2-way bass-reflex system in an ABS cabinet
- 100 V or 8 Ω operation, selectable
- 16 cm bass speaker with coated carbon fibre cone
- 30 mm dome tweeter with horn front attachment
- Front grille with water-repellent gauze
- Recessed connection terminal with cover plate and high-strength cable gland
- Metal parts and wall bracket made of stainless steel
- Ball-proof according to DIN 18032, Part 3

Model	PAB-6WP/WS
Total power rating	180 W
Power rating (RMS)	100/50/25 W
Frequency range	42-19,000 Hz
Sensitivity	90 dB/W/m
Protection class	IP45
Admiss. ambient temp.	-10 °C to +40 °C
Dimensions	200 x 370 x 240 mm
Weight	7.1 kg
Inputs	screw terminal

