

KM-26735

Order No. 0112460



Speaker stand, with flat diecast base (Ø 450 mm).

- Decorative and space-saving design
- Robust steel version, mat black lacquered
- Height adjustable in 4 steps (110-178 cm), with locking pin, additionally secured via locking screw
- 35 mm spigot
- Max. load/central weight concentration: 20 kg
- Weight: 9.64 kg
- Delivery consists of 2 boxes



KM-21302

Order No. 0112030



Telescopic speaker stand

- Robust steel version, mat black lacquered
- Crank handle with push-button for unlocking and locking screw
- Adjustable height: 138-218 cm
- 35 mm spigot with integrated M10 threaded bushing
- Max. load/central weight concentration: 40 kg
- Weight: 7.5 kg
- Type approved by TÜV (Technical Inspection Authority, Germany)



PAST-280SET

Order No. 0111990

Speaker stand set, consisting of two aluminium stands PAST-280/SW with locking system and a nylon tripod bag. For specifications, please refer to the individual items.



PAST-164SET

Order No. 0111970

Speaker stand set, consisting of two aluminium stands PAST-164/SW and a nylon tripod bag. For specifications, please refer to the individual items.



PAST-125SET

Order No. 0118910

Speaker stand set, consisting of two steel stands PAST-125/SW and a nylon tripod bag. For specifications, please refer to the individual items.



PAST-122SET

Order No. 0118710

Speaker stand set, consisting of two steel stands PAST-122/SW and a nylon tripod bag. For specifications, please refer to the individual items.



KM-21367

Order No. 0112140



Distance tube, with patented expanding mandrels 'ring lock' for a secure and low-resonance connection via plastic expanding jaws at the top and M20 threaded bolt at the bottom.

- For stand inserts with standard diameter
- Mounting plate with M20 inside thread KM-24116 is available at option
- Black lacquered steel tube version
- Height adjustable in 3 steps (98-137 cm), with locking screw
- Weight: 2.56 kg



KM-21366

Order No. 0112040



Distance tube, with patented expanding mandrels on both sides ('ring lock') for a secure and low-resonance connection via movable plastic splints.

- For stand inserts with standard diameter
- Black lacquered steel tube version
- Height adjustable in 4 steps (95-137 cm), with locking screw
- Weight: 2.34 kg



PAST-28/SW

Order No. 0118900

Distance tube, for stand inserts with standard diameter.

- Black lacquered steel tube version
- Height adjustable in 3 steps (83-123 cm), with locking pin
- Load capacity: 30 kg
- Weight: 1.78 kg



PAST-25/SW

Order No. 0129870

Distance tube, for stand inserts with standard diameter.

- Black lacquered steel tube version
- Height adjustable in 5 steps (86-134 cm), with locking pin
- Load capacity: 30 kg
- Weight: 1.4 kg

