



T H E  
H I R S C H  
E F F E K T

## DM-9

Order No. 0237211

**Dynamic microphone**, for stage and vocals.

- Supercardioid polar pattern
- Neodymium version
- Active Handling Noise Cancelling technology (AHNC) for minimising handling noise
- Humbucker coil for minimising electromagnetic interference
- Aluminium body
- Supplied with microphone holder

Model	DM-9
Polar pattern	supercardioid
System	dynamic
Audio frequency range	50-18,000 Hz
Nominal impedance	600 Ω
Sensitivity	2 mV/Pa
Max. sound pressure	142 dB
Housing material	aluminium
Dimensions	Ø 55 mm x 181 mm
Weight	330 g
Connection	XLR, bal.



## DM-9S

Order No. 0237212

**Dynamic microphone**, for stage and vocals.

- Supercardioid polar pattern
- Neodymium version
- Active Handling Noise Cancelling technology (AHNC) for minimising handling noise
- Humbucker coil for minimising electromagnetic interference
- Innovative low-noise slide potentiometer switch
- Aluminium body
- Supplied with microphone holder

Model	DM-9S
Polar pattern	supercardioid
System	dynamic
Audio frequency range	50-18,000 Hz
Nominal impedance	600 Ω
Sensitivity	2 mV/Pa
Max. sound pressure	142 dB
Housing material	aluminium
Dimensions	Ø 55 mm x 181 mm
Weight	330 g
Connection	XLR, bal.

