

Your first recording studio

You have got an idea for the perfect sound, are playing the greatest session of your life, but no chance of recording this masterpiece? The new USB recording interfaces MX-110 and MX-210 are the perfect solution. Thanks to versatile connection facilities and individual settings, you can easily transform your PC or Mac into your own recording studio and achieve a great sound. No matter whether on tour or at home: you provide the inspiration, IMG STAGELINE takes care of the equipment.

MX-210

Order No. 0203170



2-channel USB recording interface

- Integrated USB audio interface (will be identified and addressed as an external sound card)
- Full-duplex USB port (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC and for recording mixings onto a PC
- 2 mono input channels with XLR input (mic) and 6.3 mm input (switchable mic/line)
- Selectable 20 dB attenuation and LED level display
- Input channels switchable mono/stereo
- 1 additional stereo input
- 1 x 6.3 mm jack output L/R
- 1 x 3.5 mm jack stereo output
- Adjustable headphone output
- +48 V phantom power, can be activated as required for each channel
- Stereo LED level display
- Robust metal housing of compact size



Model	MX-210
Mic input	2.5 mV, 2 x 3-pole XLR
Line input	45 mV, 1 x 6.3 mm jack
	11 kΩ (line)/460 kΩ (inst.)
Aux input	1.25 V, 1 x 3.5 mm jack
Master output	500 mV, 2 x 6.3 mm jack L/R
Aux output	500 mV, 1 x 3.5 mm jack
Headphones	≥ 16 Ω, 1 x 3.5 mm jack
Frequency range	20-20,000 Hz
THD	≤ 0.03%
Crosstalk	92 dB
Power supply	via USB interface ≈ 5 V/500 mA
Dimensions	160 x 50 x 110 mm
Weight	634 g

MX-110

Order No. 0203160



1-channel USB recording interface

- Integrated USB audio interface (will be identified and addressed as an external sound card)
- Full-duplex USB port (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC and for recording mixings onto a PC
- 1 mono input channel with XLR input (mic) and 6.3 mm input (switchable mic/line)
- Selectable 20 dB attenuation and LED level display
- 1 additional stereo input
- 1 x 6.3 mm jack output L/R
- 1 x 3.5 mm stereo jack output
- Adjustable headphone output
- +48 V phantom power, can be activated as required
- Stereo LED level display
- Robust metal housing of compact size



Model	MX-110
Mic input	2.5 mV, 1 x 3-pole XLR
Line input	45 mV, 1 x 6.3 mm jack
	11 kΩ (line)/460 kΩ (inst.)
Aux input	1.25 V, 1 x 3.5 mm jack
Master output	500 mV, 1 x 6.3 mm jack L/R
Aux output	500 mV, 1 x 3.5 mm jack
Headphones	≥ 16 Ω, 1 x 3.5 mm jack
Frequency range	20-20,000 Hz
THD	≤ 0.03%
Crosstalk	92 dB
Power supply	via USB interface ≈ 5 V/500 mA
Dimensions	120 x 50 x 110 mm
Weight	498 g