

### MD-6000

Order No. 0221260

#### DJ stereo headphones

- Closed system
- Turnable folding earpieces
- Padded ear cushions and headband
- 3 m helix cable with single-sided cable inlet
- Gold-plated 3.5 mm plug with 6.3 mm adapter

Model	MD-6000
Headphone driver	neodymium, Ø 50 mm
Type of transducer	dynamic
Max. input power	100 mW
Transmission range, headphones	20-22,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	110 dB/mW
Cable	3 m, single-sided cable inlet
Plug	3.5 mm plug, gold-plated
Adapter	6.3 mm plug, gold-plated
Weight w/o cable	280 g



### MD-5000DR

Order No. 0220860

**Stereo headphones**, for applications with drums and in the studio.

- Perfectly closed system for suppressing ambient noise
- Good bass reproduction
- Extra secure fit
- Padded ear cushions
- 3 m helix cable with single-sided cable inlet
- Right-angle 3.5 mm plug, gold-plated, with thread for a secure connection to supplied 6.3 mm adapter

Model	MD-5000DR
Headphone driver	neodymium, Ø 40 mm
Type of transducer	dynamic
Max. input power	500 mW
Transmission range, headphones	10-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	105 dB/mW
Cable	3 m, single-sided cable inlet
Plug	3.5 mm plug, gold-plated
Adapter	6.3 mm plug, gold-plated
Weight w/o cable	365 g



### MDH-6300

Order No. 0221090

#### Mono hand-held DJ headphone

- Powerful neodymium magnet driver Ø 50 mm
- Closed system
- Movable earpiece
- Padded ear cushion
- Ergonomic padded handle
- Removable helix connection cable (1.3-2.8 m) with latchable XLR inline jack and right-angle 6.3 mm stereo plug
- Supplied with transport bag

Model	MDH-6300
Headphone driver	neodymium, Ø 50 mm
Type of transducer	dynamic
Max. input power	3,500 mW
Transmission range, headphones	10-22,000 Hz
Nominal impedance, headphones	46 Ω
Headphone sensitivity	96 dB/mW
Cable	1.3-2.8 m
Plug	6.3 mm plug
Weight w/o cable	152 g

