

Small, smaller, FLAT

Even if your songs are great, the stages you play on may not always be that great. Little space, modest sound; there are many challenges an artist has to face on stage every day. We have developed the FLAT monitor series exactly for this scenario: smaller than some shoebox but still with a full and transparent monitor sound for stage applications, your rehearsal room and anywhere you need to hear yourself clearly.

FLAT-M200

Order No. 0259876



Active PA stage monitor speaker system, 300 W

- Flat and very compact full range system
- Fitted with 4 x 10 cm (FaitalPRO, 4 x 4") full range speaker with neodymium magnets
- Class D amplifier system
- Sound pressure at nominal power: 122 dB
- Indication of signal and limiter
- Volume control and tone control
- Balanced line/mic input and feed-through output
- High-quality multiplex wooden cabinet with protective metal grille
- 2 x M10 and 2 x M6 threaded inserts for stand adapter or mounting device
- Supplied with clamp for mounting, e.g. onto a microphone stand

Model	FLAT-M200
Total output power	300 W
Power rating (RMS)	200 W
Frequency range	70-20,000 Hz
Input signal	25 mV/28 kΩ (line, bal.), 6 mV/20 kΩ (mic, bal.)
Sensitivity	98 dB/W/m
Housing material	multiplex
Mounting device	2 x M10 threaded insert, 2 x M6 threaded insert
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/356 VA
Dimensions	320 x 150 x 250 mm
Weight	4.11 kg
Inputs	1 x comb. XLR/6.3 mm (line/mic)
Outputs	1 x XLR link out



FLAT-M100

Order No. 0259590



Active PA stage monitor speaker system, 200 W

- Flat and very compact full range system
- Fitted with 2 x 10 cm (FaitalPRO, 2 x 4") full range speaker with neodymium magnets
- Class D amplifier system
- Sound pressure at nominal power: 116 dB
- Indication of signal and limiter
- Volume control and tone control
- Balanced line/mic input and feed-through output
- High-quality multiplex wooden cabinet with protective metal grille
- 2 x M10 and 2 x M6 threaded inserts for stand adapter or mounting device
- Supplied with clamp for mounting, e.g. onto a microphone stand

Model	FLAT-M100
Total output power	200 W
Power rating (RMS)	100 W
Frequency range	90-20,000 Hz
Input signal	16 mV/28 kΩ (line, bal.), 5 mV/20 kΩ (mic, bal.)
Sensitivity	97 dB/W/m
Housing material	multiplex
Mounting device	2 x M10 threaded insert, 2 x M6 threaded insert
Power supply	~ 230 V/50 Hz/175 VA
Dimensions	265 x 120 x 192.5 mm
Weight	2.4 kg
Inputs	1 x comb. XLR/6.3 mm (line/mic)
Outputs	1 x XLR link out

