

C-RAY/8

Order No. 0255630



Active column PA speaker system with DSP, 800 W

- Compact full range system with bass-reflex subwoofer and two column modules
- 2 x 20 cm (8") bass speaker, 12 x 7.6 cm (3") full range speaker and 2 x 2.5 cm (1") tweeter in a closed cabinet
- 2-channel class D amplifier system with 2 x 400 W
- DSP-controlled functions for crossover network, equalizer and limiter
- Sound pressure at nominal power: 115 dB, music: 118 dB, peak: 122 dB
- 4-channel mixer
- Continuously adjustable sound characteristics
- Mono selector switch
- Indication of signal, limiter and clip
- Feed-through outputs, rec out and mix output
- High-quality wooden cabinet with protective metal grille
- No cables, components attached via twist-and-lock mechanism
- Supplied w/o protective cover set C-RAY/8BAG, available at option

Model	C-RAY/8
Total output power	800 W
Power rating (RMS)	DSP-controlled 400 W (200+200) bass: 200 W mid-high range: 200 W
Frequency range	50-20,000 Hz
THD	< 0.1%
S/N ratio	80 dB
Input signal	750 mV/22 kΩ (line), 20 mV/2 kΩ (mic, bal.), 40 mV/2 kΩ (comb.), 200 mV/22 kΩ (aux)
Number of speakers	16
Sensitivity	95 dB/W/m
Beam angle	hor. 120°, vert. 30°-90° var.
Power supply	~ 230 V/50 Hz/510 VA
Dimensions	250 x 1,730 x 400 mm
Weight	23 kg
Inputs	2 x comb. XLR/6.3 mm (line L/R) 1 x comb. XLR/6.3 mm (mic) 1 x comb. XLR/6.3 mm (combo) 1 x RCA (aux L/R) 1 x 3.5 mm jack (aux L/R)
Outputs	1 x RCA (rec out, L/R) 1 x XLR, par. out 1 x XLR, MIX out



C-RAY/8BAG

Order No. 0255690

Protective cover set, for C-RAY/8, consisting of a bag for the satellites and a bag for the subwoofer. With carrying handles and shoulder strap.



C-RAY/8EXT

Order No. 0255700

Intermediate piece, for C-RAY/8.

- Increases mounting height of column satellite modules by 57 cm
- No cables, components attached via twist-and-lock mechanism
- Dimensions: 85 x 605 x 107 mm
- Weight: 1.34 kg

