Components

Speaker Technology


AIRMT-130


Order No. 01 3200




High-end Air Motion Transformer tweeter, 60 W, 8 Ω

- Tweeter based on the principle of Air Motion Transformer
- High-performance neodymium magnet system
- Fine, dynamic and brilliant reproduction of the high frequencies
- Folded cone made of Kapton and aluminium
- High power capability and high efficiency
- For use from 3,000 Hz on
- Robust aluminium front panel








AIRMT-85


Order No. 01.3190




High-end Air Motion Transformer tweeter, 20 W, 4 Ω

- Tweeter based on the principle of Air Motion Transformer
- High-performance neodymium magnet system
- Fine, dynamic and brilliant reproduction of the high frequencies
- Folded cone made of Kapton and aluminium
- High efficiency
- For use from 2,500 Hz on
- Robust aluminium front panel








RBT-56


Order No. 01 321



Hi-fi ribbon tweeter, 10 W, 4 Ω

- Magnetostatic tweeter of compact size
- Neodymium magnet system
- Fine and brilliant reproduction of the high frequencies
- \bullet Round cone with Kapton and aluminium film
- For use from 5,000 Hz on
- Plastic sound diffuser panel (front)







Model	AIRMT-130	AIRMT-85	RBT-56	
Impedance (Z)	8 Ω	4 Ω	4 Ω	
Frequency range	2,500-30,000 Hz	2,000-30,000 Hz	5,000-40,000 Hz	
Power rating (RMS)	60 W	20 W	10 W	
Peak music power output (MAX)	120 W	40 W	20 W	
Sensitivity	98 dB/W/m	92 dB/W/m	90 dB/W/m	
DC resistance (Re)	5.2 Ω	3.8 Ω	3.5 Ω	
Mounting cutout	71 x 111 mm	Ø 66 mm	Ø 40 mm	
Dimensions	90 x 130 x 38 mm	Ø 85 mm x 36 mm	56.5 mm	
Weight	0 585 kg	0.3 kg	0.035 kg	