Components

Speaker Technology

SP-17/4


Order No. 10.3680



Universal speaker, 30 W, 4 Ω

- For general applications and replacement purposes
- High power capability
- To be used in the bass-midrange





SP-13/4


Order No. 10.3660



Universal speaker, 20 W, 4 Ω

- For general applications up to the PA range
- Wide bandwidth radiation





SP-10/4


Order No. 10.3640



Universal speaker, 15 W, 4 Ω

- Speaker of high power capability for wide bandwidth applications
- Reproduction from approx. 80 Hz on





SP-10/4S

Order No. 10.3650






Universal speaker, 15 W, 4 Ω

- Magnetic shielding
- Wide bandwidth speaker of high power capability
- Reproduction from approx. 80 Hz on





SP-8/4SQ






Universal speaker, 10 W, 4 Ω

- For standard wide bandwidth appli-
- Sound pressure from approx. 100 Hz





SP-8/4SQS










Universal speaker, 10 W, 4 Ω

- Magnetic shielding
- For wide bandwidth applications
- Sound pressure from approx. 100 Hz





SP-8/4

Order No. 10.3600






Universal speaker, 10 W, 4 Ω

- For wide bandwidth applications
- Sound pressure from approx. 100 Hz





SP-7/4SO


Order No. 10.3580



Universal speaker, 4 W, 4 Ω

- For standard applications in the miniature speaker range
- Sound pressure from approx. 200 Hz





C268

Full specifications can be found on our website www.monacor-international.com

K20-192CO_05_Lautsprecher_EN_OK.indd 268 01.08.2019 11:00:24