

Components

Stage and Audio Accessories

HSE-140/SK

Order No. 23.5530

Ultra-light headband microphone, for young artists.

- Small headband design, adjustable
- Omnidirectional polar pattern
- High-quality back electret cartridge
- 3-pole mini XLR connection
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Compatible with all TXS-...HSE pocket transmitters with 3-pole mini XLR connection

- External power supply e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

Model	HSE-140/SK
Polar pattern	omnidir.
System	back electret
Audio frequency range	20-20,000 Hz
Nominal impedance	1 kΩ
Sensitivity	8 mV/Pa
Max. sound pressure	130 dB
Power supply	≈ 1.5-9 V
Weight	8 g
Connection	3-pole mini XLR



HSE-152A/SK

Order No. 23.5170

Ultra-light headband microphone

- Cardioid polar pattern
- High-quality back electret cartridge
- Plug with latching device
- Supplied with adapters for the TXS-...HSE series (3-pole mini XLR) and pocket transmitters from JTS (4-pole mini XLR)
- Excellent feedback rejection
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Removable sweat-proof connection cable with 2.5 mm stereo plug (replacement connection cable: HSE-70C)

- Optional adapters allow application with devices from other manufacturers
- External power supply e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

Model	HSE-152A/SK
Polar pattern	cardioid
System	back electret
Audio frequency range	20-20,000 Hz
Nominal impedance	1.5 kΩ
Sensitivity	1.8 mV/Pa
Max. sound pressure	130 dB
Power supply	≈ 1.5-9 V
Weight	7 g
Connection	2.5 mm stereo plug 2 connecting adapters



HSE-152/SK

Order No. 23.4280

Ultra-light headband microphone

- Cardioid polar pattern
- High-quality back electret cartridge
- 3-pole mini XLR connection
- Excellent feedback rejection
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Compatible with all pocket transmitters TXS-...HSE with 3-pole mini XLR connection

- External power supply, e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

Model	HSE-152/SK
Polar pattern	cardioid
System	back electret
Audio frequency range	20-20,000 Hz
Nominal impedance	1.5 kΩ
Sensitivity	1.8 mV/Pa
Max. sound pressure	130 dB
Power supply	≈ 1.5-9 V
Weight	7 g
Connection	3-pole mini XLR



HSE-150A/SK

Order No. 23.5160

Ultra-light headband microphone

- Omnidirectional polar pattern
- High-quality back electret cartridge
- Plug with latching device
- Supplied with adapters for the TXS-...HSE series (3-pole mini XLR) and pocket transmitters from JTS (4-pole mini XLR)
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Removable sweat-proof connection cable with 2.5 mm stereo plug (replacement connection cable: HSE-70C)
- Optional adapters allow application with devices from other manufacturers

- External power supply e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

Model	HSE-150A/SK
Polar pattern	omnidir.
System	back electret
Audio frequency range	20-20,000 Hz
Nominal impedance	1 kΩ
Sensitivity	8 mV/Pa
Max. sound pressure	130 dB
Power supply	≈ 1.5-9 V
Weight	7 g
Connection	2.5 mm stereo plug 2 connection adapters

