

PROJECT Line

INC-4000BX

Order No. 18.0127



PROJECT Line 4 megapixel network colour camera, with integrated micro SD recorder, wide dynamic range function and day/night function.

- Viewing angle: 53-135° with VGM-288ASIR, 9-53° with VGM-850ASIR
- C/CS mount thread
- Supplied w/o lens
- Connection for DC-controlled lenses
- Image compression: H.265, H.264, MJPEG
- Integrated micro SD card recorder (for media up to 128 GB, not supplied)
- Alarm input and alarm output
- Audio inputs and audio output
- Power is provided via Power over Ethernet (PoE) or optional power supply

Compatible with PROJECT Line network video recorders NWR-801POE, NWR-1608POE and NWR-3216POE, ONVIF.

| Model | INC-4000BX |
|-----------------------|--|
| Image sensor | 8.5 mm (1/2") CMOS, progressive scan |
| Number of pixels | 2592 x 1520 pixels max. |
| Resolution | 4 MP |
| Lens | not supplied |
| Min. illumination | 0.01 lx (colour) 0 lx (B/W) |
| Webserver | integrated |
| Video streaming | triple |
| Power supply | PoE or = 12 V/300 mA ~ 24 V/150 mA |
| Admiss. ambient temp. | -10 °C to +50 °C |
| Weight | 405 g |
| Other features | 1 x alarm input, 1 x alarm output |
| Ethernet | RJ45, 10/100 Mbps |
| Audio | 3 x 3.5 mm jack (in/out) |
| Video | BNC |



INC-5360DF

Order No. 18.0123



PROJECT Line 5 megapixel fisheye network camera, with 360° panorama view and professional day/night function.

- Fisheye lens (1.5 mm)
- Due to 3 super-bright LEDs, suitable for application in the dark, IR operating range: 10 m with optimum reflection
- Integrated micro SD card recorder (for media up to 128 GB, not supplied)
- Image compression: H.265, H.264, MJPEG
- Video motion detector function
- Power is provided via Power over Ethernet (PoE) or via optional power supply

Compatible with PROJECT Line network video recorders NWR-801POE, NWR-1608POE and NWR-3216POE, ONVIF.

| Model | INC-5360DF |
|-----------------------|---|
| Image sensor | 12.7 mm (1/2.5") CMOS, progressive scan |
| Number of pixels | 2560 x 1920 pixels max. |
| Resolution | 5 MP |
| Lens | 1.5 mm/1:1.2 |
| Min. illumination | 0.1 lx (colour) 0 lx (B/W) |
| Webserver | integrated |
| Video streaming | dual |
| Power supply | PoE or = 12 V/700 mA |
| Admiss. ambient temp. | -10 °C to +50 °C |
| Weight | 420 g |
| Other features | IR LED, WDR, 3D DNR |
| Ethernet | RJ45, 10/100 Mbps |
| Audio | 1 x RCA (in/out) |



INC-4312BDVM

Order No. 18.0125



PROJECT Line 4 megapixel network colour dome camera, with integrated micro SD card recorder, webserver and professional day/night function.

- Weatherproof outdoor housing
- Motorised zoom lens (2.7-12 mm)
- Viewing angle: 35-95°
- Due to 15 super-bright LEDs, suitable for application in the dark, IR operating range: 30 m, with optimum reflection
- Integrated micro SD card recorder (for media up to 128 GB, not supplied)
- Image compression: H.265, H.264, MJPEG
- Video motion detector function
- Power is provided via Power over Ethernet (PoE) or via optional power supply

Compatible with PROJECT Line network video recorders NWR-801POE, NWR-1608POE and NWR-3216POE, ONVIF.

| Model | INC-4312BDVM |
|-----------------------|--------------------------------------|
| Image sensor | 8.5 mm (1/2") CMOS, progressive scan |
| Number of pixels | 2592 x 1520 pixels max. |
| Resolution | 4 MP |
| Lens | 2.7-12 mm/1:1.2 |
| Min. illumination | 0.01 lx (colour) 0 lx (B/W) |
| Webserver | integrated |
| Video streaming | triple |
| Power supply | PoE or = 12 V/420 mA |
| Admiss. ambient temp. | -30 °C to +60 °C |
| Weight | 875 g |
| Other features | 1 x alarm input, 1 x alarm output |
| Ethernet | RJ45, 10/100 Mbps |
| Audio | 1 x RCA (in/out) |
| Video | BNC (test output) |

