

INC-4757PTZ

Order No. 18.0006

**PROJECT Line 3 megapixel PTZ speed colour dome camera**

- Weatherproof outdoor housing
- Maximum resolution: 2048 x 1536 pixels (25 fps max.)
- Motorised zoom lens (4.7-56.4 mm)
- Viewing angle: 8-70°
- 360° pan (endless), -10° to +90° tilt
- Pan speed: 0.1-180°/s (manual), tilt speed: 0.1-90°/s (manual)
- Due to 6 infrared LEDs, suitable for application in the dark. For this purpose, the camera switches to B/W operation (IR operating range: 100 m, with optimum reflection)
- Integrated micro SD card slot (for media up to 128 GB, not supplied)
- Autotracking function
- 2 alarm inputs, 1 alarm output
- 1 audio input, 1 audio output

Compatible with PROJECT Line network video recorders NWR-801POE, NWR-1608POE and NWR-3216POE, ONVIF.

Model	INC-4757PTZ
Image sensor	9.07 mm (1/2.8") CMOS, 3 megapixels
Number of pixels	2048 x 1536 pixels
Resolution	3 MP
Lens	4.7-56.4 mm/1:1.6-3.5, motorised zoom lens
Min. illumination	0 lx with IR illumination
Websserver	integrated
Video streaming	triple
Power supply	= 12 V/22 W max. via optional power supply or PoE
Admiss. ambient temp.	-40 °C to +60 °C
Weight	1.5 kg
Other features	IP66, infrared LED, 3D DNR, DWDR
Ethernet	RJ45, 10/100 Mbps
Audio	1 x RCA (in), 1 x RCA (out)

**INC-2037PHC**

Order No. 18.9932

**PROJECT Line 2 megapixel modular network colour camera, with integrated SD card recorder and webservice.**

- Fixed-focus pinhole lens (3.7 mm)
- Progressive scan image sensor for images without field distortions
- Digital noise reduction (3D DNR) for improving the image quality in difficult lighting conditions and also for saving hard disk capacities when recording with digital recorders
- Due to the extended dynamic range of the wide dynamic range function (WDR), an application is also possible in unfavourable backlighting conditions
- Integrated SD card slot (for media up to 128 GB, not supplied)
- Multilingual on-screen menu control (OSD)
- Two-way audio transmission
- Supplied with camera mount
- 0.5 m connection cable for power supply, audio (3.5 mm), network (RJ45) and alarm
- Power is provided via power supply (PSS-600E), available at option

Compatible with PROJECT Line network video recorders NWR-801POE, NWR-1608POE and NWR-3216POE, ONVIF.

Model	INC-2037PHC
Image sensor	9.07 mm (1/2.8") CMOS, 2 megapixels
Number of pixels	1920 x 1080 pixels max.
Resolution	2 MP
Lens	3.7 mm/1:2.0
Min. illumination	0.05 lx (colour), 0.01 lx (B/W)
Websserver	integrated
Video streaming	dual
Power supply	= 12 V/250 mA
Admiss. ambient temp.	-10 °C to +50 °C
Weight	180 g
Other features	2 x alarm input, 1 x alarm output
Ethernet	RJ45, 10/100 Mbps
Audio	1 x 3.5 mm jack (in/out)

