

Monitors

TFT-1002LED

Order No. 18.4900



LCD colour monitor with LED backlight, for surveillance systems and multimedia applications.

- Visible diagonal screen size: 25.65 cm (10.1")
- 2 x HDMI™ video input (Full HD 1080p)
- VGA input
- Viewing angle: 170° horizontal/vertical
- Contrast ratio: 800:1
- Brightness: 350 cd/m², 16.2 million colours
- Built-in speakers (2 x 2 W)
- Picture-in-picture function (PIP)
- Operation via on-screen menu (OSD) and supplied infrared remote control
- Metal housing and metal base
- Perforated rear panel according to VESA-75 standard
- Supplied with VGA cable, audio cable and matching power supply

| Model | TFT-1002LED |
|-----------------------|--|
| Colour system | PAL/NTSC |
| Screen diagonal | 25.65 cm (10.1") |
| Aspect ratio | 16:10 |
| Resolution | hor. 1280 x vert. 800 pixels |
| Video input | 1 Vpp/75 Ω |
| Video output | 1 Vpp/75 Ω |
| Power supply | via encl. power supply |
| Admiss. ambient temp. | 0-40 °C |
| Dimensions | 255 x 220 x 96 mm |
| Weight | 1.7 kg |
| Connections | 2 x HDMI™ 1 x VGA 1 x USB 1 x BNC (video in) 1 x RCA L/R (audio in) 1 x BNC (video out) |



TFT-800LED

Order No. 18.9020



LCD colour monitor with LED backlight, for surveillance systems and multimedia applications.

- Visible diagonal screen size: 20.3 cm (8")
- HDMI™ video input (Full HD 1080p)
- VGA input
- Viewing angle: 150° horizontal, 145° vertical
- Contrast ratio: 700:1
- Brightness: 500 cd/m², 16.2 million colours
- Built-in speaker (2 W)
- Operation via on-screen menu (OSD) and supplied infrared remote control
- Supplied with base, HDMI™ cable, audio cable and matching power supply

| Model | TFT-800LED |
|-----------------------|---|
| Colour system | PAL/NTSC |
| Screen diagonal | 20.3 cm (8") |
| Resolution | hor. 1024 x vert. 600 pixels |
| Audio input | 0.7 V/30 Ω (3.5 mm jack) |
| Video input | 1 Vpp/75 Ω |
| Power supply | via encl. power supply |
| Admiss. ambient temp. | 0-40 °C |
| Dimensions | 210 x 151 x 36 mm |
| Weight | 850 g |
| Connections | 1 x HDMI™ 1 x VGA 1 x BNC (video in) 1 x 3.5 mm jack (audio in) 1 x USB |



HYB-700TEST

Order No. 18.0108

Multifunction tester, for installation and testing of AHD, TVI, CVI, SDI, CVBS and IP cameras.

- Integrated colour LCD screen
- Diagonal screen size: 17.5 cm (7")
- Integrated cable tester
- Power is provided via enclosed power supply or integrated 7.4 V rech. lithium polymer battery
- RS485/RS422 interface for PTZ cameras with PELCO D protocol and PELCO P protocol
- RJ45 jack for testing UTP cables
- 12 V power supply output for camera or converter
- USB charging port
- BNC jack in/out for camera image (720p, 1080p)

- HDMI™ input and output
- Audio input and audio output via 3.5 mm jack
- Integrated micro SD card slot (for media up to 32 GB)
- Multilingual on-screen menu (OSD)
- Rubber protective frame with carrying handle
- Supplied with protective bag and carrying strap, plug-in power supply, connection cable
- Dimensions: 270 x 150 x 43 mm
- Weight: 900 g

