

Specifications

SMART Board® 7075 Pro interactive display with iQ and Intel® Compute Card

Model SBID-7375P

Overview

The SMART Board[®] 7075 Pro interactive display with iQ and Intel[®] Compute Card is the hub of your meeting room. PC-free embedded computing provides one-touch access to collaborative tools, including a whiteboard, wireless screen sharing and a web browser. With minimal network integration, there's no need for wires, cables or manual software and firmware updates.



Install an Intel Compute Card in the appliance to provide a fully functional Windows® 10

solution at your fingertips. Choose from three different compute card options to provide a consistent room-to-room Windows Full HD experience.

The 75" 4K ultra-high-definition LED display provides optimal image clarity and wide viewing angles. With the Pen ID[™] feature, you can assign different appearances to the four pens and write or draw over any application in digital ink.

Object Awareness[™] allows you to perform mouse functions with your finger, write in digital ink with the pen, and erase with your palm or eraser—all without switching tools or modes. You can use a variety of gestures in applications, and four users can write or draw at the same time.


See smarttech.com for more information.



As an ENERGY STAR[®] certified signage display, the SMART Board 7075 Pro interactive display with iQ and Intel Compute Card meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

Dimensions and weights¹

Dimensions



Weight

174 lb. (79 kg)

Shipping dimensions (including pallet) 75 3/8" × 54 1/4" × 11 3/4" (191.6 cm × 137.8 cm × 30 cm)

Shipping weight 227 lb. (103 kg)

Hardware

Interaction

Touch technology	HyPr Touch™ (Hybrid Precision Touch) proprietary hybrid system, which greatly improves upon its InGlass™ core by optimizing both touch and pen performance, resulting in virtually no lag and zero contact detect height
Multitouch capabilities	Up to 16 simultaneous interaction points (combination of 10 finger touch points, four pen touch points and two eraser touch points)
Object Awareness	Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger, eraser or palm.
Pen ID	Four people can write independently and simultaneously, using different colored ink.
Display	
Туре	LED
Aspect ratio	16:9
Optimal resolution	3840 × 2160 at 60 Hz
Horizontal frequency (typical)	135 kHz
Vertical frequency (typical)	60 Hz
Contrast ratio (typical)	5000:1

 ^1All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

SPECIFICATIONS SMART BOARD 7075 PRO INTERACTIVE DISPLAY WITH IQ AND INTEL COMPUTE CARD – MODEL SBID-7375P

Brightness (maximum)	360 cd/m ²
Pixel dimensions	0.429 mm × 0.429 mm
Gamut	72% of NTSC
Viewing angle	178°
Response time (typical)	8 ms
100BASE-T Ethernet	Two external ports for a four-port Gigabit Ethernet switched network connecting the interactive display and the iQ appliance to an external network and an external device, such as a computer
Presence detection	Dual sensors that reduce startup time and power consumption during inactivity
Audio	10 W integrated speakers (×2)
Noise level	<30 dBA
Included cables and accessories	iQ appliance Intel Compute Card Country-specific power cable USB cable Pen (×4) Eraser
iQ appliance	
Wireless technology	Bluetooth $^{\circ}$ 4.0 dual mode (backwards compatible with Bluetooth 2.1 + EDR)
Capture options	Establish a Bluetooth wireless connection with a supported mobile device (see below) by scanning the interactive display's unique QR code
Intel Compute Card features	See iQ appliance with Intel Compute Card for SMART Board interactive displays specifications (smarttech.com/kb/171263)
Supported languages	English French German Italian Japanese Korean Norwegian Russian Simplified Chinese Spanish Swedish Traditional Chinese Vietnamese
Mounting holes	For a standard VESA 600 mm × 400 mm mounting plate
Mounting bracket depth	Lower mounting holes 13 3/4" (35 cm) from the bottom of the interactive display Minimum depth of 2" (5.1 cm) for all components on the back of the interactive display for airflow

Connectors

Connector panel	OPS slot (for the iQ appliance) Stereo 3.5 mm out S/PDIF out VGA input connectors VGA in Stereo 3.5 mm in USB Type-B HDMI 1 input connectors HDMI 2.0 in USB Type-B Display Port input connectors in USB Type-B USB Type-A ² RJ45 (×2)
Convenience panel Bottom	HDMI 2 input connectors HDMI 1.4 in USB Type-B USB Type-A (×2) AC power in AC power out RS-232 in RS-232 out
HDCP support	Version 1.4/2.2

Installation requirements

Interactive display See the SMART Board 7000 and 7000 Pro series interactive displays installation and maintenance guide (smarttech.com/kb/171164)

IMPORTANT

The display needs an internet connection for downloading and installing important updates. Ask the network administrator to confirm that the network has been correctly configured for the iQ experience. For more information about network configuration, see Connecting a SMART display with the iQ experience to a network.

SMART kapp® app

Apple devices iOS 9 or later operating system software 50 MB of storage iPhone 4S or later Third-generation iPad or later First-generation iPad mini or later Fifth-generation iPod touch or later

²For service use only

Android [™] devices	Android 4.4.4 (KitKat) or later operating system 50 MB of storage (internal or SD card) 1024 MB of RAM 720p or better screen resolution Bluetooth 2.1 + EDR 2 maggapixed or better root facing somern (recommended)
	3 megapixel or better rear-facing camera (recommended)
SMART kapp viewer	
Mobile	Safari for iOS 9 or later operating system software
	Chrome [™] for Android 39.0.2171.93 or later
Desktop	Internet Explorer® 10 or later
	Chrome 39.0.2171.95 or later
	Firefox [®] 34.0.5 or later
	Safari 8.0 or later

Room computers and guest laptops

General requirements	See SMART Meeting Pro software release notes
4K UHD	Graphics card that can support 3840 × 2160 resolution at 60 Hz and that has 1 GB DDR 5 memory See Minimum requirements for Ultra High Definition or 4K on your interactive flat panel
Mini-computers	
General requirements	See SMART Meeting Pro software release notes
Dimensions	Smaller than 10" × 10" × 2" (25.4 cm × 25.4 cm × 5.1 cm)
Weight	Less than 10 lb. (4.5 kg)
Mounting	VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern

Cable requirements

HDMI	Maximum length: 23' (7 m)
	NOTES
	 Use only certified HDMI cables that have been tested to support the performance standard you require.
	• The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.
Display Port	Display Port 1.2 compliant or better Maximum length: 23' (7 m)
USB	Maximum length: 16' (5 m)
Important	Using cables that exceed these maximum lengths can produce unexpected results, such as degraded picture quality or USB connectivity. Refer to <i>Installation best practices for SMART products</i> (smarttech.com/kb/171035) for comprehensive information about cables and extensions for SMART hardware products.

Storage and operating requirements

Power requirements	100V to 240V AC, 50 Hz to 60 Hz
Interactive display and iG	appliance power consumption at 77°F (25°C)
Standby mode	22–24 W
Normal operating	160 W
Maximum operating	173 W
Standalone interactive display power consumption at 77°F (25°C)	
Standby mode	1.8 W
Normal operating (out-of-box)	135 W
Operating temperature	41–95°F (5–35°C)
Storage temperature	-4–140°F (-20–60°C)
Humidity	5–80% relative humidity, non-condensing

Certification and compliance

Regulatory certification	EU RED and LV Directives, ISED, cUL, FCC, UL, RCM, CITIC, TRA
Environmental compliand	ce
European Union	REACH, RoHS, WEEE, Battery and Packaging
U.S.	CONEG Packaging, California Prop 65
Regulatory models	SBID-7075 and ID7075-1

Purchasing information

Order numbers	
SBID-7375P-PENT	Black-framed SMART Board 7075 Pro interactive display with iQ, Intel Compute Card (with Pentium® N4200 processor), one SMART Meeting Pro software room license and 10 SMART Meeting Pro software personal licenses
SBID-7375P-M3	Black-framed SMART Board 7075 Pro interactive display with iQ, Intel Compute Card (with Intel Core™ m3-7Y30 processor), one SMART Meeting Pro software room license and 10 SMART Meeting Pro software personal licenses
SBID-7375P-I5	Black-framed SMART Board 7075 Pro interactive display with iQ, Intel Compute Card (with Intel Core™ i5-7Y57 processor), one SMART Meeting Pro software room license and 10 SMART Meeting Pro software personal licenses

SBID-7375P-PENT-W	White-framed SMART Board 7075 Pro interactive display with iQ, Intel Compute Card (with Pentium® N4200 processor), one SMART Meeting Pro software room license and 10 SMART Meeting Pro software personal licenses
SBID-7375P-M3-W	White-framed SMART Board 7075 Pro interactive display with iQ, Intel Compute Card (with Intel Core™ m3-7Y30 processor), one SMART Meeting Pro software room license and 10 SMART Meeting Pro software personal licenses
SBID-7375P-I5-W	White-framed SMART Board 7075 Pro interactive display with iQ, Intel Compute Card (with Intel Core™ i5-7Y57 processor), one SMART Meeting Pro software room license and 10 SMART Meeting Pro software personal licenses
Optional accessories	
WM-SBID-501	Fixed wall mount for SMART Board interactive displays
Other	See smarttech.com/accessories
Warranty	Three-year limited equipment warranty
Extended warranty	
EWY1-SBID-7375P	One-year warranty extension
EWY2-SBID-7375P	Two-year warranty extension

smarttech.com/support smarttech.com/contactsupport

^{© 2018} SMART Technologies ULC. All rights reserved. SMART Meeting Pro, SMART kapp, Pen ID, Object Awareness, HyPr Touch, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. Intel, Pentium and Core are trademarks of Intel Corporation in the U.S. and/or other countries. IPhone, iPad, iPod touch and Safari are trademarks of Apple Inc., registered in the U.S. and other countries. Google Play, Android and Chrome are trademarks of Google Inc. The Bluetooth word mark is owned by the Bluetooth SIG, Inc. and any use of such marks by SMART Technologies ULC is under license. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. 11/2018.