



ATS-10TM

Order No.: 0243510

Price upon request

PRODUCTINFOS

16-channel Mono PLL Audio Transmission System, 863-865 MHz

- Suitable as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Wireless transmissions of audio signals with one transmitter and one receiver are also possible
- Due to the small frequency spacing in this free frequency range, a simultaneous operation of not more than two transmitters is recommended (with optimum conditions, up to 7 transmitters max. are possible)
- Licence-free in the EU

Transmitter,

for microphone applications.

- 16 selectable channels
- Integrated microphone
- Supplied with additional electret tie clip microphone
- Status indication of rech. battery

- Operating positions: on/standby/off
- Volume level control, belt clip
- Transmitting power: ≤ 10 mW (EIRP), operating range: approx. 190 m
- Power supply via 2 x 1.2 V NiMH rech. battery AA size (not supplied)
- Dimensions: 65 x 92 x 25 mm
- Weight: 78 g

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

ATS-10TM

General information

-

Description	16-channel mono PLL audio transmitter
Carrier frequency range	863-865 MHz
Channels	16
Admiss. ambient temp.	0-40 °C

Specifications transmitter

-

Transmitting power	≤ 10 mW
Operating range	≈ 190 m
Power supply transmitter	2 x 1.2 V NiMH rech. battery AA size
Width transmitter	65 mm
Height transmitter	110 mm
Depth transmitter	25 mm
Weight transmitter	78 g
Connections transmitter	3.5 mm mono jack (microphone)