



ATS-16T

Order No.: 24.4690

EUR 245,00

RRP *

PRODUCTINFOS

Professional 16-channel Mono PLL Audio Transmission System, 863-865 MHz

- Suitable as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Wireless transmissions of audio signals with one transmitter and one receiver are also possible
- Simultaneous operation of up to 8 transmitters with different frequencies (dep. on distance of transmitter, stationary RF sources of interference and other local conditions)
- Licence-free in the EU

16-channel PLL transmitter,

for microphone operation and line audio signals.

- Integrated microphone
- Supplied with additional electret tie clip microphone

- Audio line input via 3.5 mm mono jack
- Status indication of rech. battery, indication of carrier signal
- Volume level control, belt clip
- Transmitting power: ≤ 10 mW (EIRP), operating range: approx. 50 m
- Power supply via 2 x 1.2 V NiMH rech. battery AA size (not supplied) or low-voltage jack (5 V)
- Dimensions: 66 x 111 x 35 mm
- Weight: 85 g

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

ATS-16T

Type	16-channel mono PLL audio transmitter
Carrier frequency range	863-865 MHz
Admiss. ambient temp.	0-40 °C
Transmitting power	≤ 10 mW
Operating range	50 m
Power supply transmitter	2 x 1.2 V NiMH rech. battery AA size, low-voltage jack (5 V)
Width transmitter	66 mm
Height transmitter	111 mm
Depth transmitter	35 mm
Weight transmitter	85 g
Connections transmitter	3.5 mm mono jack (microphone), 3.5 mm mono jack (line in)

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.