



ATS-42T

Order No.: 0254570

Price upon request

PRODUCTINFOS

40-channel Mono PLL Voice Transmission System, 863-865 MHz

- Economy tour guide system
- Narrow-band frequency range which has been perfectly adapted to voice transmissions. Thus, a parallel operation of up to 12 different channels is possible without any interference
- Licence-free in the EU

40-channel PLL transmitter,

for microphone applications.

- Supplied with additional electret tie clip microphone
- LCD for indicating channel and battery status
- Channel autolock function
- Lanyard
- Transmitting power: ≤ 10 mW (EIRP), operating range: approx. 210 m
- Power supply via 2 x 1.2 V NiMH rech. battery AA size (not supplied)
- Dimensions: 66 x 102 x 26 mm

- Weight: 55 g

Licence-free in the EU.

Matching chargers TXA-800PS, TXA-12C or TXA-36C are available at option.

TECHNICAL SPECIFICATIONS

ATS-42T

General information

Description	40-channel mono PLL transmitter
Carrier frequency range	863-865 MHz
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	≤ 10 mW
Operating range	210 m
Power supply transmitter	2 x 1.2 V NiMH rech. battery AA size
Width transmitter	66 mm
Height transmitter	102 mm
Depth transmitter	26 mm
Weight transmitter	55 g
Connections transmitter	3.5 mm jack (microphone)