



ATS-60T

Order No.: 0257670

Price upon request

PRODUCTINFOS

24-channel mono PLL voice transmission system, 823-832 MHz and 863-865 MHz

- Robust tour guide system, easy to use, with a high operating range and long running time of up to 12 hours
- Well-suited, e.g. for riding lessons

24-channel PLL transmitter

- Supplied with electret tie clip microphone
 - LCD for indicating channel, frequency, level, signal and battery status
 - Belt clip
 - Transmitting power
-
- 823-832 MHz: ≤ 50 mW (EIRP), operating range: approx. 300 m
 - 863-865 MHz: ≤ 10 mW (EIRP), operating range: approx. 240 m

- Power supply via rechargeable lithium-ion battery: 3.7 V/2,400 mAh
- Dimensions: 50 x 102 x 29 mm
- Weight: 112 g

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

TECHNICAL SPECIFICATIONS

ATS-60T

General information

Description	24-channel mono PLL transmitter
Carrier frequency range	823-832 MHz, 863-865 MHz
Operating time	12 h
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	$\leq 50 \text{ mW} / \leq 10 \text{ mW}$
Operating range	240 m
Power supply transmitter	rech. lithium-ion battery, 3.7 V/2,400 mAh
Width transmitter	50 mm
Height transmitter	102 mm
Depth transmitter	29 mm
Weight transmitter	112 g
Connections transmitter	3.5 mm jack (microphone)