



## AXC-2036DF

Order No.: 0184560

**Price upon request**

### PRODUCTINFOS

#### **High-performance camera with high luminous sensitivity for indoors and outdoors**

With the Starlight camera from the HYBRID Line, you get a compact and extremely efficient camera. Thanks to infrared and a very high luminous sensitivity of 0.001 lx, the AXC camera models provide high-quality HD recordings, even with low light.

In night vision, the IR operating range of the camera is between 10 to 20 metres. The resolution of 2 megapixels allows you to see even small and moving details in difficult lighting conditions.

Dustproof and waterproof according to IP66.

#### **HYBRID Line mini colour dome camera**

- Weatherproof outdoor housing
- Fixed-focus lens (3.6 mm)
- Viewing angle: 80°
- Resolution: 2 megapixels
- Due to 16 infrared LEDs, suitable for application in the dark. For this purpose, the camera switches to B/W operation (IR operating range: 10-20 m, with optimum resolution)
- Matching power supply (PSS-1210DC) is available at option

## TECHNICAL SPECIFICATIONS

### AXC-2036DF

#### Camera

	-
Design	mini dome
Image sensor	8.5 mm ( $\frac{1}{3}$ ") CMOS
Number of pixels	1920 x 1080 pixels max.
Resolution	1080p
Lens	3.6 mm/1:1.2
Viewing angle	80°
Min. illumination	0 lx with IR illumination
Protective class	IP66
Power supply	DC 12 V/350 mA
Operating voltage	DC 12 V
Admiss. ambient temp.	-10 °C to +50 °C
Dimensions	Ø 116 mm x 91 mm
Width	Ø 116 mm
Height	91 mm
Weight	350 g
Other features	IP66, IR LED, AGC, AWB, DNR
Video	TVI, AHD, CVBS