



AXC-2812BVM

Order No.: 0180101

Price upon request

PRODUCTINFOS

High-performance camera with high luminous sensitivity for indoors and outdoors

With the Starlight camera from the HYBRID Line, you get a compact and extremely efficient camera. Thanks to infrared and a very high luminous sensitivity of 0.001 lx, the AXC camera models provide high-quality HD recordings, even with low light.

In night vision, the IR operating range of the camera is between 30 to 50 metres. The resolution of 2 megapixels allows you to see even small and moving details in difficult lighting conditions.

Dustproof and waterproof according to IP66.

HYBRID Line colour camera

- Weatherproof outdoor housing
- Motorised zoom lens (2.8-12 mm)
- Viewing angle: 35-85°
- Resolution: 2 megapixels
- Due to 50 infrared LEDs, suitable for application in the dark. For this purpose, the camera switches to B/W operation (IR operating range: 30-50 m, with optimum reflection)
- Matching power supply (PSS-1210DC) is available at option

TECHNICAL SPECIFICATIONS

AXC-2812BVM

Camera

Design	-
Image sensor	bullet
Number of pixels	9 mm (1/2.8") CMOS, 2 megapixels
Resolution	1920 x 1080 pixels max.
Lens	1080p
Viewing angle	2.8-12 mm/1:1.2, motorised zoom lens
Min. illumination	35-85°
Protective class	0 lx with IR illumination
Power supply	IP66
Operating voltage	DC 12 V/480 mA
Admiss. ambient temp.	DC 12 V
Dimensions	-20 °C to +50 °C
Width	Ø 109 mm x 284 mm
Height	Ø 109 mm
Weight	284 mm
Other features	1 kg
Video	IP66, IR LED, AGC, AWB, DNR
	TVI, AHD, CVI, CVBS