



# AXR-108

Order No.: 0184520

**Price upon request**

## PRODUCTINFOS

### 8-channel HYBRID Line digital video recorder

- Automatic recognition of applied camera technology: analogue (960p), AHD (720p/1080p), TVI (1080p) and network-based
- Video compression: H.264
- Bandwidth: 48 Mbps
- Network connection, access via web browser
- HDMI™ video output (Full HD 1080p)
- VGA output
- 2 x USB 2.0 interface for exporting data onto a USB flash drive and for connecting USB mouse
- Remote access possible via many smartphones. Please read the notes under Service/Downloads at [www.monacor-international.com](http://www.monacor-international.com)
- Smart Home Ready
- Video motion detector, 12 x 15 sensor surfaces
- 3 recording qualities
- Recording time depends on recording rate, recording quality and hard disk capacity
- Manual recording, alarm-controlled, time-controlled or motion-triggered recording
- Quick search by time list, event list or alarm list
- Password protection
- Brightness, colour, contrast and focus can be adjusted for each channel
- PTZ cameras can be controlled (PELCO D, PELCO P)
- 8 x alarm input, 1 x alarm output
- 8 x audio input, 1 x audio output
- Supplied with infrared remote control, USB mouse and software package
- OSD: German, English, French, Spanish, Polish and other languages
- Instruction manual: German, English, French, Italian

Supplied w/o hard disks.

Matching SATA hard disks are available at option, supports 1 x 8 TB.

**The app/software is a free offer from a third-party provider and not subject to the warranty of MONACOR INTERNATIONAL. In case of any problems, please contact the publisher of the app.**

## TECHNICAL SPECIFICATIONS

### AXR-108

#### Video recorder

	-
Video inputs	8 x BNC
Video outputs	1 x HDMI™ 1 x VGA
Audio inputs	8 x RCA
Audio outputs	1 x RCA
Resolution	1850 x 1080 pixels (25 fps)
Video compression	H.264
Recording	200 images/s max.
Menu adjustments	on-screen menu (OSD)
Recording mode	manual, alarm, timer, motion detector
Search mode	date and time, event
Lettering	OSD
Security	password protection
Video loss detection	available
Alarm inputs	8
Alarm outputs	1
Signal device	integrated
Interfaces	RS-485, USB 2.0, LAN (RJ45)
Hard disks	optional, 1 x 8 TB max. (SATA)
Power supply	DC 12 V/5 A via encl. power supply
Operating voltage (possible alternative)	DC 12 V
Power supply (possible alternative)	DC 5 A
Admiss. ambient temp.	0-40 °C
Dimensions	300 x 48 x 225 mm
Width	300 mm
Height	48 mm

**AXR-108**

Depth	225 mm
Weight	1.4 kg