



AXZ-408BVM

Order No.: 0180117

Price upon request

PRODUCTINFOS

HYBRID Line video surveillance set,

consisting of 8-channel HYBRID Line digital video recorder AXR-108 and 4 x HYBRID Line colour camera AXZ-2812BVM.

8-channel HYBRID Line digital video recorder AXR-108

- Including 1 TB hard disk (SATA)
- Automatic recognition of applied camera technology: analogue (960p), AHD (720p/1080p), TVI (1080p) and network-based (up to 8 MP)
- Video compression: H.264
- Network connection, access via web browser
- HDMI™ video output (Full HD 1080p)
- VGA output
- 2 x USB 2.0 interface for exporting data onto a USB flash drive and for connecting USB mouse
- Smart Home Ready
- Video motion detector, 12 x 12 sensor surfaces
- 8 x alarm input, 1 x alarm output
- 8 x audio input, 1 x audio output

- Power is provided via enclosed power supply
- Supplied with power supply, infrared remote control, USB mouse and software package

4 x HYBRID Line colour camera AXC-2812BVM

- Weatherproof outdoor housing, IP66
- Motorised zoom lens (2.8-12 mm)
- Viewing angle: 35-85°
- Resolution: 2 megapixels
- Due to 50 infrared LEDs, suitable for application in the dark. For this purpose, the camera switches to B/W operation (IR operating range: 30-50 m, with optimum reflection)
- Power is provided via enclosed power supply
- Supplied with 18 m connection cable

For further specifications, please refer to the individual items.

Built-in hard disk.

Remote access possible via smartphone apps (RXCam, RCXCam Link, RXCamLinkHD) for various systems.
Please read the notes under Service/Downloads at www.monacor-international.com.

TECHNICAL SPECIFICATIONS

AXZ-408BVM

Video recorder	AXR-108
Video inputs	8 x BNC
Video outputs	1 x HDMI™ 1 x VGA
Audio inputs	8 x RCA
Audio outputs	1 x RCA
Resolution	1850 x 1080 pixels (25 fps)
Video compression	H.264
Recording	200 images/s max.
Menu adjustments	on-screen menu (OSD)
Recording mode	manual, alarm, timer, motion detector
Search mode	date and time, event
Lettering	OSD
Security	password protection

AXZ-408BVM

Video loss detection	available
Alarm inputs	8
Alarm outputs	1
Signal device	integrated
Interfaces	RS-485, USB 2.0, LAN (RJ45)
Hard disks	optional, 1 x 8 TB max. (SATA)
Power supply	DC 12 V/5 A via encl. power supply
Operating voltage (possible alternative)	DC 12 V
Power supply (possible alternative)	DC 5 A
Admiss. ambient temp.	0-40 °C
Dimensions	300 x 48 x 225 mm
Width	300 mm
Height	48 mm
Depth	225 mm
Weight	1.4 kg

AXZ-408BVM

Camera	AXC-2812BVM
Design	bullet
Image sensor	9 mm (1/2.8") CMOS, 2 megapixels
Number of pixels	1920 x 1080 pixels max.
Resolution	1080p
Lens	2.8-12 mm/1:1.2, motorised zoom
Viewing angle	35-85°
Min. illumination	0 lx with IR illumination
Protective class	IP66
Power supply	DC 12 V/480 mA
Operating voltage	DC 12 V
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 109 mm x 284 mm
Width	Ø 109 mm
Height	284 mm
Weight	350 g
Other features	IP66, IR LED, AGC, AWB, DNR
Video	TVI, AHD, CVI, CVBS

