



## CD-292USB

Order No.: 0212790

**Price upon request**

### PRODUCTINFOS

**Professional dual DJ CD and MP3 player,**

with USB 2.0 interface.

Due to the combined device access technology (CDA), both drives can access the same USB reproduction medium simultaneously. Thus, e.g. pre-fader listening to the tracks is possible during the current reproduction without having to stop the PA application in the function room. In addition, a second USB storage medium can be connected for common use or for split operation (each drive uses its own medium).

- USB storage media can be connected directly (e.g. USB hard disk, USB flash drive)
- Capable of multi-partition (NTFS, FAT, HFS+)
- Supports ID3 tags and CD text
- Supports play lists (M3U, XML, WPL)
- Anti-shock system (CDDA and MP3 CD)
- Pitch control:  $\pm 8/\pm 16/\pm 100\%$
- Master tempo
- Pitch bending
- Seamless loop/reloop function
- Autoloop
- Loop editing and autoloop editing
- Scratch effect
- Automatic beat counter (switchable to manual)

- Speed search for tracks and folders
- Repeat folder
- Relay play
- Cue function
- 2-way hot cue
- Automatic cue
- Fader start
- Track programming, 99 tracks
- Folder navigation
- Jog dial
- Sleep mode
- Switchable display of the running time of one track as well as the remaining running time of one or all tracks
- 482 mm (19") rack installation
- Audio CD/CD-R/MP3 CD

### Beat 12/2011

“The CD-292USB definitely knows how to improve the reputation of rack-based DJ solutions. The unit appears to be professional in every way ... a high-quality system ... is more than just a suitable unit for playing tracks.”

## TECHNICAL SPECIFICATIONS

### CD-292USB

Description	Dual DJ CD and MP3 player
Media	CD, MP3, USB
Frequency range	20-20,000 Hz
THD	< 0.1%
Channel separation	> 80 dB
Dynamic range	> 80 dB
S/N ratio	> 80 dB
Output, analogue	2 V
Power supply	~ 230 V/50 Hz/40 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	40 VA
Admiss. ambient temp.	0-40 °C
Dim., player mech.	482 x 90 x 260 mm, 2 RS
Dim., control panel	482 x 90 x 85 mm, 2 RS

**CD-292USB**

Weight

6.5 kg

Connections

2 x RCA L/R,  
2 x 3.5 mm jack (fader start),  
2 x cable, 8-pole mini DIN, length: 1.2 m (control  
connection)