



## PAAR PAIR 70W

# **CRB-165PS**

Order No.: 0131220

### **Price upon request**

#### **PRODUCTINFOS**

Kick bass speakers which perfectly combine a modern finish with the application of approved and optimised materials.

The design of the polypropylene cones are of a special structure, with high damping and moisture-proof material also provide a better stability.

#### Pair of car hi-fi bass-midrange speakers, 35 W, 4 $\Omega$

- · Bass-midrange speaker and powerful kick bass driver
- Polypropylene cone of special design, especially resistant to pulsed peaks
- Very rigid dust cap
- · Basket with textured coating
- Gold-plated connections
- Frequency range: 50-4,500 Hz
- Ideal for combination with additional tweeters
- Mounting dimensions: Ø 144 x 70 mm
- Outside dimensions: Ø 165 mm x 71 mm
- Type 165



# **TECHNICAL SPECIFICATIONS**

#### CRB-165PS

Impedance (Z)  $4 \Omega$ 

Frequency range f3-4,500 Hz

Resonant frequency (fs) 65 Hz

Power rating (RMS) 35 W

Peak music power output (MAX) 70 W

Sensitivity 89 dB/W/m

Suspension compl. (Cms) 0.32 mm/N

Moving mass (Mms) 14.5 g

Mech. Q factor (Qms) 4.54

Electr. Q factor (Qes) 1.25

Total Q factor (Qts) 0.99

Equivalent volume (Vas) 11 l

DC resistance (Re)  $$3.6\ \Omega$$ 

Force factor (BxL) 4.20 Tm

Voice coil induct. (Le) 0.6 mH

Voice coil diameter Ø 25 mm

Voice coil former aluminium

Linear excursion  $(X_{MAX})$   $\pm 3 \text{ mm}$ 

Eff. cone area (Sd) 137 cm<sup>2</sup>

Magnet weight 280 g

Mounting cutout Ø 146 mm

Mounting depth 70 mm

Mounting hole diameter  $\emptyset$  155.5 mm

Dimensions Ø 165 mm x 71 mm

Outside diameter Ø 165 mm

Width Ø 165 mm

Depth 71 mm Admiss. ambient temp. 0-40 °C

Weight 0.95 kg

Packing unit 2

Type of speaker 165