



EDL-165AB/WS

Order No.: 0163650

Price upon request

PRODUCTINFOS

PA A/B ceiling speaker,

with EN 54-24 certification for systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 13 cm full range speaker with dual voice coil
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Quick mounting with stainless steel spring clips
- Metal housing with fire protection cover and protective metal front grille
- Ball-proof according to DIN 18032, Part 3

TECHNICAL SPECIFICATIONS

EDL-165AB/WS

Transmission method	100 V
Frequency range	80-19,000 Hz

EDL-165AB/WS

Power rating (RMS)	2 x 6/3/1.5 W
Sensitivity	93 dB/W/m
Max. rated SPL	101 dB
Radiation angle, horizontal	180°
Radiation angle, vertical	180°
Mounting cutout	Ø 140-150 mm
Mounting depth	90 mm
Dimensions	Ø 170 mm x 95 mm
Outside diameter	Ø 170 mm
Width	Ø 170 mm
Depth	95 mm
Admiss. ambient temp.	0-40 °C
Weight	1.4 kg
Packing unit	1
Type of speaker	130