



ELAXR-8

Order No.: 0180009

Price upon request

PRODUCTINFOS

8-channel ECO Line digital video recorder

- Automatic recognition of applied camera technology: analogue (960p), AHD (720p/1080p), TVI (1080p)
- Video compression: H.265
- Network connection, access via web browser
- HDMI™ video output (Full HD 1080p)
- VGA output and BNC output
- 2 x USB 2.0 interface for exporting data onto a USB flash drive and for connecting USB mouse
- Remote access possible via many smartphones. Please read the notes under Service/Downloads at www.monacor-international.com
- Video motion detector, 18 x 22 sensor surfaces
- Recording time depends on recording rate, recording quality and hard disk capacity
- Manual recording, motion-triggered or time-controlled recording
- Search by time list, event list or alarm list
- Password protection
- Brightness, colour, contrast and focus can be adjusted for each channel
- PTZ cameras can be controlled (PELCO D, PELCO P)
- Smart Home Ready
- Supplied with power supply, USB mouse and software package
- OSD: German, English, French, Spanish, Polish and other languages
- Instruction manual: German and English

Supplied w/o hard disks.

Matching SATA hard disks are available at option, supports 1 x 6 TB

Remote access possible via smartphone app (SuperLive Plus) for various systems. Please read the notes under Service/Downloads at www.monacor-international.com.

TECHNICAL SPECIFICATIONS

ELAXR-8

Video recorder

	-
Video inputs	8 x BNC 1 x HDMI™
Video outputs	1 x VGA 1 x BNC
Audio inputs	1 x RCA
Audio outputs	1 x RCA
Resolution	1850 x 1080 pixels (12 fps)
Video compression	H.265
Recording	8 x 12 fps
Menu adjustments	on-screen menu (OSD)
Recording mode	manual, timer, motion detector
Search mode	date and time, event
Lettering	OSD
Security	password protection
Video loss detection	available
Signal device	integrated
Interfaces	RS485, USB2.0, LAN (RJ45)
Hard disks	optional, 1 x 6 TB max. (SATA)
Power supply	via encl. power supply
Operating voltage (possible alternative)	DC 12 V
Power supply (possible alternative)	DC 2 A
Admiss. ambient temp.	0-40 °C
Dimensions	255 x 42 x 233 mm
Width	255 mm
Height	42 mm
Depth	233 mm
Weight	735 g