



ELIP-2812BWDR

IP66 D/N POE HD WDR VARIO ZOOM











Order No.: 0180161

Price upon request

PRODUCTINFOS

ECO Line 2 megapixel network colour camera

with wide dynamic range function (WDR).

- · Weatherproof outdoor housing
- Zoom lens (2.8-12 mm)
- Viewing angle: 33-90°
- Resolution: 2 megapixels
- Due to the extended dynamic range of the wide dynamic range function (WDR), an application is also possible in unfavourable backlighting conditions
- Due to 20 infrared LEDs, suitable for application in the dark. For this purpose, the camera switches to B/W operation (IR operating range: 30-40 m, with optimum reflection)
- Privacy masking function
- Video motion detector function
- Smart Home Ready
- Power is provided via optional power supply (PSS-1210DC) or via Power over Ethernet (PoE)

Compatible with ECO Line network video recorders ELIPR-4, ELIPR-8, ELIPR-16, ONVIF.



TECHNICAL SPECIFICATIONS

ELIP-2812BWDR

Camera -

Design bullet

Image sensor 9 mm (1/2.8") CMOS, Sony Number of pixels $1920 \times 1080 \text{ pixels max.}$

Resolution 1080p

Lens 2.8-12 mm/1:1.2

Viewing angle 33-90°

0.001 lx,

Min. illumination 0 lx with IR illumination

dual stream

Video streaming (1920 x 1080 pixels max.,

30 images/s)

Compression method H.265, H.264

RTSP, FTP, PPPOE, DHCP,

Protocols

DDNS, NTP, UPnP, NFS

Protective class IP66

Power supply DC 12 V/600 mA

Operating voltage DC 12 V

Admiss. ambient temp. $-10 \, ^{\circ}\text{C}$ to $+50 \, ^{\circ}\text{C}$ Dimensions $83 \times 81 \times 277 \, \text{mm}$

Width 83 mm
Height 81 mm
Depth 277 mm
Weight 875 g

Other features IP66, IR LED, AGC, BLC, 3D DNR, WDR

Ethernet RJ45, 10/100 Mbps