



ETS-120SL/WS

Order No.: 0163450

Price upon request

PRODUCTINFOS

These super slimline speaker systems

are the perfect solution whenever unobtrusive PA technology and a high-quality sound are required at the same time. These slimline array speakers were technically feasible only due to the development of new speaker systems which are a combination of flat cone speakers and magnetostatic drive. For a full range sound reproduction, the application of a subwoofer system is recommended.

Pair of line array design speakers, 4 Ω,

in slimline extruded aluminium cabinets.

- Elegant slimline design
- Cross-sectional area not much bigger than a 1 Euro coin
- New type of speaker systems with magnetostatic drive and flat cone speakers
- Very wide bandwidth reproduction with an excellent sound quality
- High transmission range due to line array system
- Connection via screw terminal
- Fine-meshed front grille with fleece lining
- Supplied with mounting brackets and connection cables

tools4music 4/2017

“Design speaker, column speaker, array speaker - the ETS-120SL/WS from MONACOR is almost invisible due to its narrow width and depth, despite its height of 1,200 mm. Thus, it is possible to implement unobtrusive PA applications in room corners and well-designed residential or commercial environments. The speaker provides an unobtrusive sound and combined with respective subwoofer support and integration into a controller-optimised setting, the fun is just beginning. You can't see anything, but it is quite impressive when the subwoofer starts to provide a powerful bass combined with the high-resolution speakers ETS-120SL/WS. Not exactly a bargain, but 'invisible speakers' for a stylish lifestyle ambience may actually be an invaluable asset. Therefore, thumbs up for an unobtrusive speaker which provides a great sound just for the ears.”

Pros and Cons

- + fine sound
- + unobtrusive appearance, super slimline design
- + neat workmanship
- + practice-oriented radiation range
- + ultra lightweight
- + supplied with extensive mounting auxiliaries

TECHNICAL SPECIFICATIONS

ETS-120SL/WS

Active/passive	passive
Total power rating	80 W
Power rating (RMS)	40 W
Impedance	4 Ω
Frequency range	120-20,000 Hz
System	line array speaker
Full range speaker	4 x (20 x 120 mm)
Number of speakers	4
Speaker size	20 x 120 mm
Sensitivity	88 dB/W/m
Max. rated SPL	103 dB
Radiation angle, horizontal	160°
Radiation angle, vertical	40°
Housing material	aluminium
Colour	white
Mounting device	screw-on bracket
Admiss. ambient temp.	0-40 °C
Dimensions	36 x 1,210 x 22 mm
Width	36 mm

ETS-120SL/WS

Height	1,210 mm
Depth	22 mm
Weight	0.95 kg
Inputs	screw terminal