



ETS-8100TW/WS

Order No.: 0163800

Price upon request

PRODUCTINFOS

High-quality weatherproof PA column speaker, IP66

- High-quality 2-way column speaker with excellent sound characteristics
- 100 V line technique or 8 Ω operation
- 8 x 7.7 cm (3") speaker with polypropylene cone
- 25 mm (1") centrally arranged dome tweeter
- 3 power taps: 60/30/15 W
- Power capability: 100 W in 8 Ω operation
- Connection is made via cable with high-strength cable gland (length: 2 m)
- Robust aluminium cabinet with plastic front protective grille
- Supplied with robust wall bracket for pivoting and tilting

TECHNICAL SPECIFICATIONS

ETS-8100TW/WS

Active/passive	passive
Transmission method	100 V

ETS-8100TW/WS

Power rating (RMS)	60/30/15 W (100 V) 100 W (8 Ω)
Impedance	8 Ω
Frequency range	110-20,000 Hz
Full range speaker	8 x Ø 77 mm
Tweeter	1
Number of speakers	9
Sensitivity	95 dB/W/m
Max. rated SPL	117 dB
Radiation angle, horizontal	70°
Radiation angle, vertical	20°
Housing material	aluminium
Colour	white
Mounting device	wall bracket
Protection class	IP66
Admiss. ambient temp.	0-40 °C
Dimensions	125 x 869 x 110 mm
Width	125 mm
Height	869 mm
Depth	110 mm
Weight	6 kg
Inputs	cable
Other features	supplied with wall bracket