



## GLS-301/GR

Order No.: 0163070

**Price upon request**

### PRODUCTINFOS

#### **Weatherproof PA garden speaker “Rock”,**

stone look, for general PA applications, e.g. in gardens, hotels, restaurants and pubs.

- Omnidirectional radiation pattern
- 100 V line technique or 8 Ω operation
- Robust, glass fibre reinforced plastic cabinet
- 2-way coaxial speaker system (200 mm bass speaker and 13 mm tweeter)
- Integrated audio transformer with 4 power taps (30/20/10/5 W)
- Connection cable with luster terminals

#### **HiFiTest 04/2013**

Price-performance: very good

“The speaker with an unobtrusive appearance and a height of about 32 cm provides a pleasant omnidirectional radiation with an extra voluminous sound.”

## TECHNICAL SPECIFICATIONS

### GLS-301/GR

Active/passive	passive
Transmission method	100 V
Total power rating	90 W
Power rating (RMS)	30/20/10/5 W (100 V) 45 W (8 $\Omega$ )
Impedance	8 $\Omega$
Frequency range	60-20,000 Hz
System	2-way
Bass speaker	200 mm
Tweeter	13 mm
Number of speakers	2
Speaker size	200 mm
Sensitivity	85 dB/W/m
Housing material	GRP
Colour	grey
Protection class	IP55
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	320 x 500 x 310 mm
Width	320 mm
Height	500 mm
Depth	310 mm
Weight	9.5 kg