

HPB-604 - Page: 1



HPB-604

Order No.: 0142490

Price upon request

PRODUCTINFOS

Car hi-fi amplifier, 4 channels, 400 W

- 4-channel power amplifier with extensive features, ideally suited for combining a stereo mid-high range system with any subwoofer or also for driving speakers in the front or rear
- Adjustable high-pass filter and low-pass filter for each channel pair
- 2-channel, 3-channel or 4-channel operation, selectable
- Variable bass boost for each channel pair
- Additional mono line out (2x), high-power input possible with FGA-22 or FGA-22HQ

TECHNICAL SPECIFICATIONS

HPB-604	
Peak output power	700 W
Power rating	400 W
Power rating at 2 Ω	4 x 100 W
Power rating at 4 Ω	4 x 75 W





HPB-604

Power rating with 4 Ω bridged operation :	2 x 200 W
Channels	4
Inputs	0.4-4 V/20 kΩ
Frequency range	20-20,000 Hz
Crossover frequency	40-300 Hz, 6 dB/oct. (low-pass filter) 40-500 Hz, 6 dB/oct. (high-pass filter)
S/N ratio	> 93 dBA
THD	< 0.2%
Operating voltage (possible alternative)	DC 12 V
Power supply (possible alternative)	50 A
Admiss. ambient temp.	0-40 °C
Width	252 mm
Height	62 mm
Depth	400 mm
Weight	3.195 kg
Connections	screw terminals (speakers) 1 x RCA L/R (line in) 1 x RCA L/R (line out)