



HSE-310/SK

Order No.: 0234120

Price upon request

PRODUCTINFOS

Professional headband microphone,

with cardioid polar pattern and a high-quality sound which is suitable for any vocal or speech application. Innovative design features ensure a maximum suppression of both the impact sound and structure-borne noise as well as an extra low acoustic feedback, very comfortable to wear.

Beige version.

- Corrosion-resistant neckband, easy to clean
- Drip ring (protects cartridge from moisture)
- Unobtrusive and secure fit due to cable routing in neck area incl. strain relief and cable bending protection
- Stable positioning
- Microphone windshield
- External power supply, e.g. via phantom power supply adapter EMA-1 or EMA-300P
- 3-pole mini XLR inline jack, matches EMA-1 or pocket transmitters TXS-...HSE

With regard to acoustic feedback, these microphones allow a particularly convenient operation due to the cardioid characteristic.

TECHNICAL SPECIFICATIONS

HSE-310/SK

Description	headband microphone
Transmission method	cable
Polar pattern	cardioid
System	electret
Audio frequency range	50-18,000 Hz
Nominal impedance	2 k Ω
Sensitivity	2.3 mV/Pa
Max. sound pressure	120 dB
Power supply	1.5-9 V
Admiss. ambient temp.	0-40 °C
Weight	18 g (w/o cable and plug)
Connection	3-pole mini XLR