



IOZ-204BV

Order No.: 0189150

Price upon request

PRODUCTINFOS

COMFORT Line video surveillance set,

consisting of a COMFORT Line 4-channel network video recorder IOR-204 and 2 x COMFORT Line 3 megapixel network colour camera IOC-2812BV.

COMFORT Line 4-channel network video recorder IOR-204

- Including 2 TB hard disk (SATA)
- Video compression for recordings: H.264, H.265
- Linux operating system for maximum operating reliability
- Automatic camera identification due to UPnP protocol
- Supports PTZ cameras
- 4 x alarm input, 1 x alarm output
- 1 x audio input, 1 x audio output
- Smart Home Ready
- Power is provided via enclosed power supply
- Supplied with infrared remote control, USB mouse and software package

2 x COMFORT Line 3 megapixel network colour camera IOC-2812BV

- Weatherproof outdoor housing
- Zoom lens (2.8-12 mm)
- Viewing angle: 35-89°
- Resolution: 2048 x 1536 pixels max.
- Due to 42 infrared LEDs, suitable for application in the dark. For this purpose, the camera switches to B/W operation (IR operating range: 30 m, with optimum reflection)
- Smart Home Ready
- Power is provided via optional power supply (PSS-1250DC) or via Power over Ethernet (PoE)
- Supplied with 2 x 20 m Cat. 5e network cable

For further specifications, please refer to the individual items.

Built-in hard disk.

Remote access possible via smartphone apps (RXCamView) for various systems. Please read the notes under Service/Downloads at www.monacor-international.com.

Digital Home 02/2017

“With the surveillance system from MONACOR, you can keep an eye on everything 24/7. The network recorder ensures a reliable recording of events in full HD image quality for several weeks on end. In this case, it allows individual options for identification and notification and is able to simultaneously control up to 4 cameras.”

Rating: top class

Price-performance: very good

Overall rating: 1.1

TECHNICAL SPECIFICATIONS

IOZ-204BV

Video recorder	IOR-204
Video inputs	4 IP-based video channels, 4 x RJ45, LAN with PoE
Video outputs	HDMI™, VGA
Audio inputs	1
Audio outputs	1
Resolution	3840 x 2160 pixels max.
Video compression	H.264, H.265
Recording	120 images/s max.

IOZ-204BV

Menu adjustments	on-screen menu (OSD)
Recording mode	alarm, motion-triggered, continuous recording, digital input, manual, timer
Alarm inputs	4
Alarm outputs	1
Interfaces	1 x RJ45 (10/100 Mbps) 3 x USB 2.0
Hard disks	optional, up to 1 x SATA II, 8 TB max.
Power supply	via encl. power supply
Admiss. ambient temp.	0-40 °C
Dimensions	300 x 53 x 227 mm
Width	300 mm
Height	53 mm
Depth	227 mm
Weight	750 g

IOZ-204BV

Camera	IOC-2812BV
Design	bullet
Image sensor	8.76 mm (1/2.9") CMOS
Number of pixels	2048 x 1536 pixels max.
Resolution	3 MP
Lens	2.8-12 mm/1:1.2
Viewing angle	35-89°
Min. illumination	0 lx with IR illumination
Video streaming	mainstream 500-12,000 kbps, substream 100-6,000 kbps
Compression method	H.265, H.264, MJPEG
Protocols	HTTP, HTTPS, TCP/IP, RTSP, DHCP, NTP, PPoE
Protective class	IP66
Power supply	DC 12 V/1 A or PoE
Operating voltage	DC 12 V
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 84 mm x 239 mm
Width	Ø 84 mm
Height	239 mm
Weight	670 g

IOZ-204BV

Other features

IP66, IR LED, AGC, AWB, DWDR

Ethernet

RJ45, 10/100 Mbps