



IOZ-408BV

Order No.: 0189170

Price upon request

PRODUCTINFOS

COMFORT Line video surveillance set,

consisting of COMFORT Line 8-channel network video recorder IOR-208 and 4 x COMFORT Line 3 megapixel network colour camera IOC-2812BV.

COMFORT Line 8-channel network video recorder IOR-208

- Including 2 TB hard disk (SATA)
- Video compression for recordings: H.264, H.265
- Linux operating system for maximum reliability
- Automatic camera identification due to UPnP protocol
- Supports PTZ cameras
- 8 x alarm input, 1 x alarm output
- 1 x audio input, 1 x audio output
- Smart Home Ready
- Power is provided via enclosed power supply
- Supplied with infrared remote control, USB mouse and software package

4 x COMFORT Line 3 megapixel network colour camera IOC-2812BV

- Weatherproof outdoor housing
- Zoom lens (2.8-12 mm)
- Viewing angle: 35-89°
- Resolution: 2048 x 1536 pixels max.
- Due to 42 infrared LEDs, suitable for application in the dark. For this purpose, the camera switches to B/W operation (IR operating range: 30 m, with optimum reflection)
- Smart Home Ready
- Power is provided via optional power supply (PSS-1250DC) or via Power over Ethernet (PoE)
- Supplied with 4 x 20 m Cat. 5e network cable

For further specifications, please refer to the individual items.

Built-in hard disk.

Remote access possible via smartphone apps (RXCamView) for various systems. Please read the notes under Service/Downloads at www.monacor-international.com.

TECHNICAL SPECIFICATIONS

IOZ-408BV

Video recorder	IOR-208
Video inputs	8 IP-based video channels, 8 x RJ45, LAN with PoE
Video outputs	HDMI™, VGA
Audio inputs	1
Audio outputs	1
Resolution	3840 x 2160 pixels max.
Video compression	H.264, H.265
Recording	120 images/s max.
Menu adjustments	on-screen menu (OSD)
Recording mode	alarm, motion-triggered, continuous recording, digital input, manual, timer
Alarm inputs	8
Alarm outputs	1
Interfaces	1 x RJ45 (10/100 Mbps) 3 x USB 2.0
Hard disks	optional, up to 1 x SATA II, 8 TB max.
Power supply	via encl. power supply

IOZ-408BV

Admiss. ambient temp. 0-40 °C

Dimensions 300 x 53 x 227 mm

Width 300 mm

Height 53 mm

Depth 227 mm

Weight 900 g

IOZ-408BV

Camera	IOC-2812BV
Design	bullet
Image sensor	8.76 mm (1/2.9") CMOS
Number of pixels	2048 x 1536 pixels max.
Resolution	3 MP
Lens	2.8-12 mm/1:1.2
Viewing angle	35-89°
Min. illumination	0 lx with IR illumination
Video streaming	mainstream 500-12,000 kbps, substream 100-6,000 kbps
Compression method	H.265, H.264, MJPEG
Protocols	HTTP, HTTPS, TCP/IP, RTSP, DHCP, NTP, PPoE
Protective class	IP66
Power supply	DC 12 V/1 A or PoE
Operating voltage	DC 12 V
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 84 mm x 239 mm
Width	Ø 84 mm
Height	239 mm
Weight	670 g
Other features	IP66, IR LED, AGC, AWB, DWDR
Ethernet	RJ45, 10/100 Mbps