



## LA-402

Order No.: 0179160

**Price upon request**

### PRODUCTINFOS

#### **Active loop amplifier,**

with dynamic compressor for setting up an inductive sound reproduction system in large rooms up to 750 m<sup>2</sup>.

Inductive transmission of audio signals allows users of hearing aids with a T-coil or inductive receivers, e.g. the LR-202, to receive audio signals. Wireless transmission is an advantage of inductive sound reproduction systems which makes it possible for the user to move freely within the loop.

Inductive sound reproduction systems are used for various applications, e.g. as a hearing aid for the hearing impaired in houses of worship, theatres, cinemas, waiting rooms and lounges, as interpreting systems, for lectures in museums, exhibitions, etc.

With inductive sound reproduction systems, an inductive loop made of a wire winding is laid on the floor, the wall or along the ceiling and is controlled by a constant current amplifier. Thus, a magnetic field is created within the loop which induces a voltage into the T-coil of the hearing aid or into the inductive receiver. In the receivers, this voltage is then converted again into an audio signal.

- Dynamic compressor
- Automatic talkover
- Metal loss correction 0-3 dB/oct.
- 3 mic/line inputs with 40 V phantom power, to be switched on additionally
- 6.3 mm input for inserting external devices
- Integrated SD card reader for reproduction of stored alarm messages
- 2-way tone control
- LED level meter
- 482 mm (19") rack installation with supplied mounting brackets

## TECHNICAL SPECIFICATIONS

### LA-402

Loop current	14 A (peak)
Loop resistance	0.2-2 $\Omega$
Room size	up to 750 m <sup>2</sup>
Inputs	mic 1.5 mV/6.8 k $\Omega$ , XLR, bal. switchable to line 630 mV/10 k $\Omega$ , XLR, bal. line 630 mV/4.7 k $\Omega$ , RCA, unbal. alarm: 2 screw terminals for connecting a switch
Outputs	Lloop: 2 screw terminals
Equalizer bass	$\pm 10$ dB, 100 Hz
Equalizer treble	$\pm 10$ dB, 10 kHz
Frequency range	50-8,000 Hz
THD	< 1%
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/230 VA
Dimensions	482 x 88 x 280 mm, 2 RS
Weight	6.97 kg