



LEDS-52MP/WWS

Order No.: 0385650

PRODUCTINFOS

Flexible LED strip, DC 24 V, warm white

Easy installation due to perfect flexibility and self-adhesive rear side which adheres to almost any kind of smooth surface, suitable for indoor and outdoor applications. Ideally suited for decorative lighting or commercial lighting. Due to small dimensions, an application is also possible at locations where standard lamps cannot be used. Features bare cable ends for direct connection to a power supply, optional DMX interfaces or LED controllers.

- Moisture-proof version
- Double-row
- Fitted with 1,200 SMD 3528 LEDs
- High luminous efficiency due to double-row LEDs
- Beam angle of each LED: 120°
- Can be cut into segments of variable size (groups of 12 LEDs)
- PU sleeving for outdoor applications, IP65
- Self-adhesive rear side
- 10 retaining clips
- Supplied on a plastic reel

TECHNICAL SPECIFICATIONS

LEDS-52MP/WWS

Luminous colour	warm white
Colour temperature	3,300 K
Luminous flux	1,320 lm
Luminous intensity	1,500 mcd
Fitted with	1,200 LEDs, SMD 3528
Beam angle	120°
Power supply	DC 24 V/3.7 A (0.9 A/m)
Operating voltage	DC 24 V
Current consumption	3.7 A
Width	12 mm
Height	4 mm
Length	5 m
Weight	348 g