



MEGA-215SUB

Order No.: 0090100

Price upon request

PRODUCTINFOS

The MEGA-215SUB

is a high-performance subwoofer for applications requiring a very powerful yet distinguished bass reproduction. The bass-reflex tube with a large vent operates with minimum friction losses. Furthermore, the arrangement of the speakers results in a sound reproduction with reverse attenuation. Stacking several speaker systems on top of each other or position them side by side to create a cluster will again improve the performance considerably.

Premium professional PA cabinet subwoofer, 4,000 W, 4 Ω

- High-power bass-reflex hybrid horn subwoofer system
- 2 x 38 cm (15", Faital) high-performance bass speaker
- Cabinet made of high-quality and extensively reinforced birch multiplex
- Durable and high-strength two-component PU coating
- Front grille with acoustic foam
- Transport cover for covering the front of the speaker cabinet
- Stacking foot grooves for horizontal or vertical stacking of several MEGA-215SUB speaker systems to create clusters
- M20 threaded plate inside the recessed grips for distance tubes, rubber feet

- 2 x NEUTRIK SPEAKON terminal, IN-OUT
- 4 x 100 mm rear castors from BLICKLE

tools4music 04/2014

“With the complete set and particularly with the new subwoofer, IMG Stage Line now offers truly impressive PA technology (which has also been developed by them). Nevertheless, the price range remains quite attractive. Anyone who becomes familiar with handling, weight and size of this impressive double 15" speaker will not be disappointed because the double version provides an even more powerful performance with quite a unique sound. Clubbers will definitely love it.”

TECHNICAL SPECIFICATIONS

MEGA-215SUB

Active/passive	passive
Transmission method	cable
Total power rating	4,000 W
Power rating (RMS)	2,000 W
Impedance	4 Ω
Frequency range	30-250 Hz
System	bass-reflex hybrid horn
Bass speaker	2 x 38 cm (15", Fital)
Number of speakers	2
Speaker size	38 cm (15")
Sensitivity	98 dB/W/m
Max. rated SPL	133 dB
Housing material	birch multiplex
Colour	black
Mounting device	M20 threaded plate
Admiss. ambient temp.	0-40 °C
Dimensions	1,050 x 500 x 650 mm (w/o castors)
Width	1,050 mm
Height	500 mm
Depth	650 mm
Weight	63 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON

